

## TECHNICAL DATA SHEET



**SLIDE®**

**PAINTABLE  
MOLD  
RELEASE**

Safe for use with all plastics  
Seguro para ser usado con todos  
los plásticos

Use where parts must be painted,  
hot stamped or metalized  
Para uso en partes que tienen  
que pintarse, estamparse al  
color o metalizarse



### Paintable Mold Release Bulk/Liquid 40001PB, 40005PB, 40055PB

#### Product Description

This paintable mold release is UL recognized and requires no special cleaning. It will not interfere with part bonding, heat sealing, laminating, ultrasonic welding or post-decorating operations. You get perfect finishes every time and more cycles per can over other comparable releases.

#### Applications

Mold Release

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Paintable Mold Release

#### Approx. Net Weight Fill per Gal.

6 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Clear Oily Colorless Liquid

#### Odor

Mild, Petroleum-like

#### Flash Point F

25 degrees

#### Flash Point C

Negative 4 degrees

#### Base Type

Paintable Silicone Fluid

#### Evaporation Rate

Fast

#### HMIS Rating

2, 3, 0, X

#### DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

96.67

#### VOC g/L (Federal)

683.05

#### VOC lbs./Gal (Federal)

5.7

#### Removal

Remove with organic or hydrocarbon solvents

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 650 degrees

#### Working Temperature C

0 to 343 degrees

#### Specific Gravity

0.698