

## TECHNICAL DATA SHEET





**Product Description** 

EpoxEase is a synthetic wax-based, non-silicone release. It is formulated to prevent the sticking commonly seen when using all-purpose release agents on epoxies, maximizing your productivity. Ideal for use on epoxy, polyester and phenolic resins and most often utilized in encapsulating and potting applications.

**Applications** 

Mold Release

**Unit Package Description** 

1, 5 and 55-gallon containers

**Generic Description** 

Mold Release for Epoxy Resins

Approx. Net Weight Fill per Gal.

9 pounds

Net Weight Fill

1 - 55 gallons

**Appearance** 

Light-brown Oily Wax

Odor

Mild. Petroleum-like

Flash Point F

None

Flash Point C

None

**Base Type** 

Wax

**Evaporation Rate** 

Fast

**HMIS Rating** 

2, 1, 0, B

**DOT Proper Shipping Name** 

Not Regulated

VOC % (Federal)

91

VOC g/L (Federal)

981.38

VOC lbs./Gal (Federal)

8.19

Removal

Remove with organic or hydrocarbon solvents

Itelliova

1

Units Per Case

Various

Case Weight (lbs)

32 to 450 degrees

**Working Temperature F** 

0 to 232 degrees

Working Temperature C

**Specific Gravity** 

1.19

