

## TECHNICAL DATA SHEET



### Econo-Spray® 3 Mold Release Bulk/Liquid 40801PB, 40805PB, 40855PB

**Product Description**

Econo-Spray® 3 contains a highly effective non-silicone release in a non-chlorinated solvent carrier system. This product is highly paintable, and will permit ultra-sonic welding of molded parts. It affords excellent release of all thermoplastics.

**Applications**

Mold Release

**Unit Package Description**

1, 5 and 55-gallon containers

**Generic Description**

Paintable Mold Release

**Approx. Net Weight Fill per Gal.**

6 pounds

**Net Weight Fill**

1 - 55 gallons

**Appearance**

Clear Oily Colorless Liquid

**Odor**

Mild, Petroleum-like

**Flash Point F**

25 degrees

**Flash Point C**

Negative 4 degrees

**Base Type**

Propylene Glycol

**Evaporation Rate**

Fast

**HMIS Rating**

2, 3, 0, X

**DOT Proper Shipping Name**

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

**VOC % (Federal)**

96.67

**VOC g/L (Federal)**

683.05

**VOC lbs./Gal (Federal)**

5.7

**Removal**

Remove with organic or hydrocarbon solvents

**Food Safety Citation (CFR)**

21CFR 178.3570

**Units Per Case**

1

**Case Weight (lbs)**

Various

**Working Temperature F**

32 to 600 degrees

**Working Temperature C**

0 to 315 degrees

**Specific Gravity**

0.698

