

TECHNICAL DATA SHEET



Urethane Mold Release Bulk/Liquid 45801PB, 45805PB, 45855PB

Product Description

Urethane Mold Release is extremely effective for all polyurethanes: rigid, semi-rigid and flexible urethane foams. Urethane mold release imparts a light, dry coating on the mold, eliminating build-up. Yet, it is so effective that it continues to work for several cycles between applications. Non-paintable formulation.

Applications

Mold Release

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Mold Release for Urethane Resins

Approx. Net Weight Fill per Gal.

7 pounds

Net Weight Fill

1 - 55 gallons

Appearance

Clear Oily Colorless Liquid

Odor

Mild. Petroleum-like

Flash Point F

25 degrees

Flash Point C

Negative 4 degrees

Silicone

Base Type

Fast

Evaporation Rate

2, 3, 0, X

HMIS Rating

_, _, _, ...

DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution,

Hazard Class - 3, Packing Group - II

VOC % (Federal)

93

VOC g/L (Federal)

666.42

VOC lbs./Gal (Federal)

5.56

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

1

Various

Case Weight (lbs)

32 to 500 degrees

Working Temperature F
Working Temperature C

0 to 260 degrees

Specific Gravity

0.698

