

TECHNICAL DATA SHEET



Aluminum Anti-Seize 48008

Product Description

Aluminum Anti-Seize Compound is a premium anti-seize lubricant containing no lead or copper for maximum resistance to the most corrosive and extreme temperature environments. It has a non-melting synthetic carrier which depolymerizes and dissipates at temperatures exceeding 400°F without leaving a carbon residue. It reduces friction and lubricates metal surfaces to 2000°F/1093°C, preventing galling and seizing as well offering protection against rust and corrosion.

Applications

Anti-Seize

Unit Package Description

8 ounce brush top container

Generic Description

Aluminum Anti-Seize

Net Weight Fill

8 net weight ounces

UPC Code

858799000806

Appearance

Aluminum Paste

Odor

None

Flash Point F

>350

Flash Point C

>176

Base Type

Petroleum Distillates

Evaporation Rate

Will not evaporate

HMIS Rating

1, 1, 0, B

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

2.1

VOC g/L (Federal)

21

VOC lbs./Gal (Federal)

0.175

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

1

Case Weight (lbs)

2

Working Temperature F

32 to 2000 degrees

Working Temperature C

0 to 1095 degrees

Propellant

N/A

Coefficient of Friction

0.098

Specific Gravity

	1.1
Penetration ASTM D217-60T	320-350
Solids Content	21%