

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.
430 S. WHEELING ROAD
WHEELING, IL 60090

PRODUCT NAME: SLIDE TAP-IT AEROSOL

EMERGENCY TELEPHONE #: 800-535-5053
INFORMATION TELEPHONE #: 847-541-7220
FAX NUMBER: 847-541-7986
PREPARED BY: JIM ARMSTRONG

REVISION DATE: 9-1-06
PRODUCT NUMBER: 40412
D.U.N.S. NUMBER: 00-299-4168

SECTION I. IDENTIFICATION

CHEMICAL NAME: SYNTHETIC LUBRICANTS SOLUTION
CHEMICAL FAMILY:
FORMULA: 40412
SYNONYMS: SLIDE TAP-IT
DOT HAZARD CLASSIFICATION: ORM-D
DOT SHIPPING NAME: CONSUMER COMMODITY
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE
IDENTIFICATION NUMBER: NONE
H.M.I.S. RATING: 1,3,0,B

SECTION II. PHYSICAL DATA

BOILING POINT: 103-190 DEGREES F.
FREEZING POINT: < -50 DEGREES F.
SPECIFIC GRAVITY: (H2O =1): .779
WEIGHT PER GALLON @ 60 F.: 6.499
VAPOR PRESSURE OF CONCENTRATE @ 70 F. (MM HG): NIL
VAPOR DENSITY (AIR =1): >1
SOLUBILITY IN WATER, % BY WT.: 20
EVAPORATION RATE (MINUTES): >1
APPEARANCE AND ODOR: YELLOW TINT, SLIGHT HYDROCARBON ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:	APPROX. WEIGHT%	CAS NUMBER:	PEL(OSHA)
PROPRIETARY LIQUID	75-85	143-28-2	NOT ESTABLISHED
PROPANE	8-14	74-98-6	1000 PPM
ALIPHATIC HYDROCARBON	8-14	64742-48-9*	300 PPM

**CONTAINS NO OZONE DEPLETING CHEMICALS

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: N/A UEL: N/A (VOLUME %)
FLASH POINT: NO FLASH
SPECIAL FIRE FIGHTING PROCEDURES: NONE
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT TEMPERATURES ABOVE 120° F.

SECTION V. REACTIVITY DATA

STABILITY: STABLE
INCOMPATIBILITY (MATERIALS TO AVOID): NONE KNOWN
HAZARDOUS COMBUSTION BY-PRODUCTS: SEE SECTION IV.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
CONDITIONS TO AVOID: TEMP. ABOVE 120° F.-DIRECT SUNLIGHT

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 300 PPM

EFFECTS OF OVEREXPOSURE

INGESTION (SWALLOWING): N/A
INHALATION: NONE
SKIN CONTACT: DEFATTING OF SKIN
EYE CONTACT: TEMPORARY IRRITATION

• **EMERGENCY AND FIRST AID PROCEDURES***

SKIN: WASH WITH SOAP AND WATER, APPLY HAND CREAM
INHALATION: REMOVE TO FRESH-AIR LOCATION AWAY FROM EXPOSURE
EYES: RINSE WITH PLENTY COOL CLEAN WATER UNTIL IRRITATION SUBSIDES

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.
WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL – CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION
VENTILATION: ADEQUATE VENTILATION RECOMMENDED
PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED
EYE PROTECTION: PROPER EYE CARE IS NEEDED IN ALL INDUSTRIAL OPERATIONS
OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM HEAT SOURCES OR DIRECT SUNLIGHT-DO NOT PUNCTURE OR INCINERATE-DO NOT DROP!
OTHER PRECAUTIONS: AVOID OVER-SPRAYING ONTO FLOORS OR SLIPPERY SURFACE MAY RESULT.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCTS SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO GE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THSES RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

<http://www.slideproducts.com/cutting.htm>