

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.
430 S. WHEELING ROAD
WHEELING, IL 60090

PRODUCT NAME: BULK ECONO-SPRAY 2 MOLD RELEASE
EMERGENCY TELEPHONE: 800-535-5053 REVISION DATE: 9-1-06
INFORMATION TELEPHONE: 847-541-7220 PRODUCT NUMBER: 407 Bulk
FAX NUMBER: 847-541-7986 D.U.N.S. NUMBER: 00-299-4168
PREPARED BY: JIM ARMSTRONG

THIS MSDS IS APPLICABLE TO: 40701B, 40705B and 40755B UNITS

SECTION I. IDENTIFICATION

CHEMICAL NAME: PHENYL-SUBSTITUTED POLYSILOXANE SOLUTION

CHEMICAL FAMILY: SILICONE FLUID

FORMULA: 40701B, 40705B, and 40755B

SYNONYMS: SLIDE ECONO SPRAY II

CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE

H.M.I.S. RATING: 2, 0, 0, G

1 GALLON SHIPPING INFORMATION:

DOT HAZARD CLASSIFICATION: ORM-D

DOT SHIPPING NAME: CONSUMER COMMODITY

IDENTIFICATION NUMBER: NONE

PACKING GROUP: N/A

5 & 55 GALLON SHIPPING INFORMATION:

DOT HAZARD CLASSIFICATION: 6.1

DOT SHIPPING NAME: TRICHLOROETHYLENE SOLUTION

IDENTIFICATION NUMBER: UN 1710

PACKING GROUP: III

SECTION II. PHYSICAL DATA

BOILING POINT: 103-105 DEGREES F.

FREEZING POINT: <-38 DEGREES F.

SPECIFIC GRAVITY (H₂O = 1): 1.42

WEIGHT PER GALLON @ 60 F.: 11.937

VAPOR PRESSURE @ 70 F. (MM HG): 59

VAPOR DENSITY (AIR = 1): >1

SOLUBILITY IN WATER, % BY WEIGHT: NIL

EVAPORATION RATE (MINUTES): >1.3

APPEARANCE AND ODOR: CLEAR LIQUID – MILD HALOGENATED HC ODOR

SECTION III. HAZARDOUS INGREDIENTS

MATERIAL:	APPROX. WT. %:	CAS NUMBER:	PEL(OSHA):
SILICONE FLUID	1	63148-62-9	N/A
MINERAL OIL	2	8042-47-5	N/A
TRICHLOROETHYLENE**	97	79-01-6	100 PPM

**)SEE SECTIONS X AND XI FOR DETAILED CAUTIONS

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: 8.0 UEL: 10.5 (VOLUME %)

FLASH POINT: NONE

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF-CONTAINED BREATHING APPARATUS

UNUSUAL FIRE & EXPLOSION HAZARDS: CONCENTRATE VAPORS FORM HCl, HF, AND TRACES OF PHOSGENE UPON PYROLYSIS

SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS

HAZARDOUS COMBUSTION BY-PRODUCTS: SEE SECTION IV

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: OPEN FLAMES AND HOT GLOWING OBJECTS

SECTION VI. HEALTH HAZARD DATE (ALSO SEE SECTIONS X & XI)

THRESHOLD LIMIT VALUE: 100 PPM

- **EFFECTS OF OVEREXPOSURE ***

INGESTION (SWALLOWING): GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING

INHALATION: EXCESSIVE INHALATION CAN CAUSE DIZZINESS, WEAKNESS, HEADACHE OR POSSIBLE UNCONSCIOUSNESS.

SKIN CONTACT: PROLONGED CONTACT CAUSES MODERATE IRRITATION, DE-FATTING

EYE CONTACT: IRRITATION, REDNESS, TEARING, BLURRED VISION

- **EMERGENCY AND FIRST AID PROCEDURES ***

SKIN: WASH WITH SOAP AND WATER - APPLY HANDCREAM

INHALATION: REMOVE TO FRESH-AIR LOCATION AWAY FROM EXPOSURE. ADMINISTER OXYGEN IF NECESSARY. DO NOT GIVE STIMULANTS. EPONEPHRINE OR EPHEDRINE MAY EFFECT HEART ADVERSELY.

EYES: FLUSH WITH LARGE AMOUNTS COLD CLEAN WATER UNTIL IRRITATION SUBSIDES

INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: DIKE SPILL, REMOVE WITH ABSORBANT TO LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

WASTE DISPOSAL METHOD: STANDARD FOR SOLVENT DRUMS. SEND TO LICENSED RECLAIMER OR APPROVED LANDFILL IN COMPLIANCE WITH APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION

VENTILATION: MECHANICAL (GENERAL) RECOMMENDED

PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED

EYE PROTECTION: PROPER EYE CARE IS NEEDED IN ALL INDUSTRIAL OPERATIONS

OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP CONTAINER CLOSED WHEN NOT IN USE. DO NOT EAT, DRINK OR SMOKE IN WORK AREA.

OTHER PRECAUTIONS: STORE INDOORS IN COOL DRY LOCATION. VAPORS ARE HEAVIER THAN AIR, AND MAY COLLECT IN LOW AREAS. DO NOT ENTER WITHOUT ADEQUATE BREATHING APPARATUS AND AN OBSERVER FOR ASSISTANCE.

SECTION X. EFFECTS OF PROLONGED EXPOSURE

TRICHLOROETHYLENE: PROLONGED EXPOSURE MAY CAUSE SKIN IRRITATION, MAY BE ABSORBED THROUGH SKIN TO SOME DEGREE. EXCESSIVE INHALATION CAUSED IRRITATION TO UPPER RESPIRATORY TRACT AND MAY INCREASE SENSITIVITY TO EPINEPHRINE, AND INCREASED MYOCARDIAL IRRITABILITY (IRREGULAR HEARTBEATS). MINIMAL ANESTHETIC EFFECTS AT LEVELS OF 200-400 PPM. DIZZINESS AT HIGHER LEVELS: AT 1000-2000 PPM UNCONSCIOUSNESS AND DEATH. CONCENTRATIONS OVER 6000 PPM ARE IMMEDIATELY HAZARDOUS TO LIFE. LC50 FOR RATS IS 12,500 PPM FOR 4 HOURS. ALCOHOL WILL ENHANCE ADVERSE EFFECTS. EXCESSIVE EXPOSURE MAY CAUSE LIVER OR KIDNEY EFFECTS; LOWER CONCENTRATIONS ABOVE ACCEPTED GUIDELINES MAY CAUSE CENTRAL OR PERIPHERAL NERVOUS SYSTEM EFFECTS.

SECTION XI. CARCINOGENIC HAZARD

CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER. PROLONGED EXPOSURE ABOVE THE OSHA PERMISSIBLE LIMITS MAY RESULT IN LIVER AND KIDNEY DAMAGE. TRICHLOROETHYLENE HAS BEEN EXTENSIVELY STUDIED FOR CHRONIC EFFECTS IN ANIMALS. WHILE THERE ARE STUDIES IN WHICH TUMORS WERE INDUCED IN MICE, THERE IS NO DOCUMENTED EVIDENCE THAT EXPOSURE TO TRICHLOROETHYLENE PRODUCES CANCER IN HUMANS. TRICHLOROETHYLENE IS LISTED IN GROUP 2A BY IARC BUT IS NOT LISTED BY NTP OR OSHA.

SECTION XII. REPORTING REQUIREMENTS

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL(S) REQUIRED TO BE REPORTED UNDER SARA TITLE III, SECTION 313: TRICHLOROETHYLENE, CAS NUMBER 79-01-6. REPORTING REQUIREMENTS UNDER CERCLA PART 302 ARE 100 POUNDS. ANY RELEASES WHICH EXCEED THE RQ MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER AT 800-424-8802.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

<http://www.slideproducts.com/mold.htm>