

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.  
430 S. WHEELING ROAD  
WHEELING, IL 60090

PRODUCT NAME: SLIDE POLYCARBONATE MR 41412N

EMERGENCY TELEPHONE: 800-535-5053  
INFORMATION NUMBER: 847-541-7220  
FAX NUMBER: 847-541-7986  
PREPARED BY: JIM ARMSTRONG

REVISION DATE: 9-1-06  
PRODUCT NUMBER: 41412N  
D.U.N.S. NUMBER: 00-299-4168

**SECTION I. IDENTIFICATION**

CHEMICAL NAME: DIMETHYLPOLYSILOXANE SOLUTION  
CHEMICAL FAMILY: SILICONE  
FORMULA: 53125  
SYNONYMS: SLIDE REGULAR  
DOT HAZARD CLASSIFICATION: ORM-D  
DOT SHIPPING NAME: CONSUMER COMMODITY  
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE  
IDENTIFICATION NUMBER: NONE  
H.M.I.S. RATING: 1,1,0,B

**SECTION II. PHYSICAL DATA**

BOILING POINT: N/A  
FREEZING POINT: <-50° F.  
SPECIFIC GRAVITY (H2O=1): 1.0  
WEIGHT PER GALLON @ 60 F.: 8.37  
BAPOR PRESSURE @ 70 F. (MM HG): N/A  
VAPOR DENSITY (AIR =1): N/A  
SOLUBILITY IN WATER, % BY WT.: NOT SOLUBLE  
PERCENT VOLATILE BY WEIGHT: 95  
EVAPORATION RATE (MINUTES): N/A  
APPEARANCE AND ODOR: CLEAR, OILY, COLORLESS LIQUID, NO ODOR

**SECTION III. HAZARDOUS INGREDIENTS**

MATERIAL:	APPROX. WEIGHT %:	CAS NUMBER:	PEL(OSHA):
SILICONE FLUID	1-10	68037-77-4	N/A
DIMETHYL ETHER	45-55	115-10-6	1000 PPM
1,1,1,2-TETRAFLUOROETHANE	45-55	811-97-2	1000 PPM

\*\*CONTAINS NO OZONE DEPLETING CHEMICALS\*\*  
ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

**SECTION IV. FIRE AND EXPLOSION HAZARD DATA**

FLAMMABLE LIMITS IN AIR: LEL: UEL: (VOLUME %)  
FLASH POINT: N/A  
AEROSOL FLAME PROJECTION TEST: NON-FLAMMABLE AS DETERMINED BY THE AEROSOL FLAME PROJECTION TEST.  
EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, FOAM  
SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS  
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT TEMPERATURES ABOVE 120 DEGREES F.

**SECTION V. REACTIVITY DATA**

STABILITY: STABLE  
INCOMPATIBILITY (MATERIALS TO AVOID): POWDERED OR ALKALINE EARTH METALS  
HAZARDOUS COMBUSTION BY-PRODUCTS: HF AND OTHER FLUORINE COMPOUNDS  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
CONDITIONS TO AVOID: OPEN FLAMES AND HIGH TEMPERATURES

---

**SECTION VI. HEALTH AND HAZARD DATA**

---

THRESHOLD LIMIT VALUE: 1000 PPM

• **EFFECTS OF OVEREXPOSURE \***

INGESTION (SWALLOWING): N/A

INHALATION: EXCESSIVE INHALATION CAN PRODUCT DIZZINESS, NAUSEA AND HEADACHE

SKIN CONTACT: CONCENTRATED SPRAY MAY CAUSE FREEZING OF SKIN AREA

EYE CONTACT: TEMPORARY IRRITATION

• **EMERGENCY AND FIRST AID PROCEDURES \***

SKIN: WASH WITH SOAP AND WATER

INHALATION: REMOVE TO FRESH AIR LOCATION

EYES: FLUSH WITH PLENTY OF WATER, CALL PHYSICIAN

---

**SECTION VII. SPILL OR LEAK PROCEDURES**

---

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.

WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

---

**SECTION VIII. SPECIAL PROTECTION INFORMATION**

---

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION

VENTILATION: ADEQUATE VENTILATION NEEDED

PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRES

EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS

OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

---

**SECTION IX. SPECIAL PRECAUTIONS**

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM DIRECT SUNLIGHT, BELOW 120' F. DO NOT DROP, PUNCTURE OR INCINERATE.

OTHER PRECAUTIONS: DO NOT SPRAY DIRECTLY INTO FLAME. DO NOT SMOKE WHILE USING PRODUCT. DO NOT SPRAY ON FLOORS.

---

**SECTION X. CARCINOGENIC HAZARD**

---

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARU, N.T.P., OSHA OR ACGIH

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

<http://www.slideproducts.com/mold.htm>