

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.  
430 S. WHEELING ROAD  
WHEELING, IL 60090

PRODUCT NAME: SLIDE UNIVERSAL RELEASE

EMERGENCY TELEPHONE: 800-535-5053  
INFORMATION TELEPHONE: 847-541-7220  
FAX NUMBER: 847-541-7986  
PREPARED BY: JIM ARMSTRONG

REVISION DATE: 9-1-06  
PRODUCT NUMBER: 42612H  
D.U.N.S. NUMBER: 00-299-4168

**SECTION I. IDENTIFICATION**

CHEMICAL NAME: SEVERELY HYDRO TREATED PARAFFINIC WHITE OIL  
CHEMICAL FAMILY: HYDROCARBON  
FORMULA: 53134  
SYNONYMS: SLIDE UNIVERSAL  
DOT HAZARD CLASSIFICATION: ORM-D  
DOT SHIPPING NAME: CONSUMER COMMODITY  
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE  
IDENTIFICATION NUMBER: NONE  
H.M.I.S. RATING: 1,1,0,B

**SECTION II. PHYSICAL DATA**

BOILING POINT: N/A  
FREEZING POINT: <-50° F. N/A  
VAPOR DENSITY (AIR = 1): N/A  
SPECIFIC GRAVITY (H2O =1): 1.0  
WEIGHT PER GALLON @ 60 F.: 8.37  
VAPOR PRESSURE @ 70 F. (MM HG): N/A  
SOLUBILITY IN WATER, % BY WT.: PARTIALLY SOLUBLE  
PERCENT VOLATILE BY WEIGHT: 96  
EVAPORATION RATE (MINUTES): N/A  
APPEARANCE AND ODOR: OILY, CREAM COLORED, SLIGHT ETHEREAL ODOR

**SECTION III. HAZARDOUS INGREDIENTS**

| MATERIAL:                 | APPROX. WT. %: | CAS NUMBER: | PEL(OSHA) |
|---------------------------|----------------|-------------|-----------|
| ALIPHATIC HYDROCARON      | 1-7            | 8042-47-5   | N/A       |
| DIMETHYL ETHER            | 40-50          | 115-10-6    | 1000 PPM  |
| 1,1,1,2 TETRAFLUOROETHANE | 40-50          | 811-97-2    | 1000 PPM  |

\*\*CONTAINS NO OZONE DEPLETING CHEMICALS\*\*  
ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY

**SECTION IV. FIRE AND EXPLOSION HAZARD DATA**

FLAMMABLE LIMITS IN AIR: LEL: 4.0 UEL: 25.0 (VOLUME %)  
FLASH POINT: N/A  
AEROSOL FLAME PROJECTION TEST: NON-FLAMMABLE AS DETERMINED BY THE AEROSOL FLAME PROJECTION TEST.  
EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, FOAM  
SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS  
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT TEMPERATURES ABOVE 120° F.

**SECTION V. REACTIVITY DATA**

STABILITY: STABLE  
INCOMPATIBILITY (MATERIALS TO AVOID): POWDERED OR ALKALINE EARTH METALS  
HAZARDOUS COMBUSTION BY-PRODUCTS: HF AND OTHER FLUORINE COMPOUNDS  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
CONDITIONS TO AVOID: OPEN FLAMES AND HIGH TEMPERATURES.

---

**SECTION VI. HEALTH HAZARD DATA**

---

THRESHOLD LIMIT VALUE: 1000 PPM

• **EFFECTS OF OVEREXPOSURE \***

INGESTION (SWALLOWING): N/A

INHALATION: EXCESSIVE INHALATION CAN PRODUCE DIZZINESS, NAUSEA AND HEADACHE

SKIN CONTACT: CONCENTRATED SPRAY MAY CAUSE FREEZING OF SKIN AREA

EYE CONTACT: TEMPORARY IRRITATION

• **EMERGENCY AND FIRST AID PROCEDURES \***

SKIN: WASH WITH SOAP AND WATER

INHALATION: REMOVE TO FRESH AIR LOCATION

EYES: FLUSH WITH PLENTY OF WATER, CALL PHYSICIAN

---

**SECTION VII. SPILL OR LEAK PROCEDURES**

---

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.

WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

---

**SECTION VIII. SPECIAL PROTECTION INFORMATION**

---

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION

VENTILATION: ADEQUATE VENTILATION NEEDED

PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED

EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS

OTHER PROTECTIVE EQUIPMENT: AS YOUR COMPANY REQUIRES

---

**SECTION IX. SPECIAL PRECAUTIONS**

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM DIRECT SUNLIGHT, BELOW 120° F. DO NOT DROP, PUNCTURE OR INCINERATE.

OTHER PRECAUTIONS: DO NOT SPRAY DIRECTLY INTO FLAME. DO NOT SMOKE WHILE USING PRODUCT. DO NOT SPRAY ON FLOORS.

---

**SECTION X. CARCINOGENIC HAZARD**

---

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARC, N.T.P., OSHA OR ACGIH.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

\*) RELEASE PRINCIPLE IN THIS PRODUCT IS APPROVED AS A DIRECT FOOD ADDITIVE UNDER FEDERAL DEFINITIONS AND STANDARDS OF IDENTITY FOR FOOD: 21 CFR 182.4521 (G.R.A.S.) GENERALLY RECOGNIZED AS SAFE.

<http://www.slideproducts.com/mold.htm>