

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.
430 S. WHEELING ROAD
WHEELING, IL 60090

PRODUCT NAME: SLIDE UNIVERSAL CYLINDER 42635N

EMERGENCY TELEPHONE: 800-535-5053
INFORMATION TELEPHONE: 847-541-7220
FAX NUMBER: 847-541-7986
PREPARED BY: MICHAEL MUTH

REVISION DATE: 09-01-03
PRODUCT NUMBER: 42635N
D.U.N.S. NUMBER: 00-299-4168

SECTION I. IDENTIFICATION

CHEMICAL NAME: PHOSPHATIZED MONO AND DYGLYCERIDES SOLUTION
CHEMICAL FAMILY: VEGETABLE OIL DERIVATIVE
FORMULA: 53134
SYNONYMS: SLIDE UNIVERSAL
DOT HAZARD CLASSIFICATION: 2.1
DOT SHIPPING NAME: COMPRESSED GAS NOS (TETRAFLUOROETHANE, DIMETHYL ETHER)
CHEMICAL ABSTRACT REGISTRY NUMBER: N/A, MIXTURE
IDENTIFICATION NUMBER: UN# 1954
REQUIRED SHIPPING LABELS: FLAMMABLE GAS
PACKING GROUP: NONE
H.M.I.S. RATING: 1,1,0,B

SECTION II. PHYSICAL DATA

DATA IN SECTION II APPLY TO CONCENTRATE BEFORE ADDING PROPELLANT
BOILING POINT: N/A
FREEZING POINT: <-50° F.
SPECIFIC GRAVITY (H2O =1): 1.0
WEIGHT PER GALLON @ 60 F.: 8.37
VAPOR PRESSURE @ 70 F. (MM HG): N/A
VAPOR DENSITY (AIR = 1): >1
SOLUBILITY IN WATER, % BY WT.: PARTIALLY SOLUBLE
PERCENT VOLATILE BY WEIGHT: 95
EVAPORATION RATE (MINUTES):
APPEARANCE AND ODOR: CLEAR, COLORLESS LIQUID, SLIGHT ETHEREAL ODOR

SECTION III. HAZARDOUS INGREDIENTS

| MATERIAL: | APPROX. WEIGHT % : | CAS NUMBER: | PEL(OSHA) |
|----------------------------------|--------------------|-------------|-----------|
| SODIUM GLYCERYL OLEATE PHOSPHATE | 1-8 | N/A | N/A |
| DIMETHYL ETHER | 47.5 | 115-10-6 | 1000 PPM |
| 1,1,1,2-TETRAFLUORETHANE | 47.5 | 811-97-2 | 1000 PPM |

ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA DIRECTORY
CONTAINS NO OZONE DEPLETING CHEMICALS

SECTION IV. FIRE AND EXPLOSION HAZARD DATA

FLAMMABLE LIMITS IN AIR: LEL: UEL: (VOLUME %)
FLASH POINT: N/A
AEROSOL FLAME PROJECTION TEST: 18" FLAME PROJECTION AS DETERMINED BY THE AEROSOL FLAME PROJECTION TEST.
EXTINGUISHING MEDIA: DRY CHEMICAL, CO2, FOAM
SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS
UNUSUAL FIRE & EXPLOSION HAZARDS: AEROSOLS MAY RUPTURE VIOLENTLY AT TEMPERATURES ABOVE 120 DEGREES F.

SECTION V. REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY (MATERIALS TO AVOID): POWDERED OR ALKALINE EARTH METALS

HAZARDOUS COMBUSTION BY-PRODUCTS: HF AND OTHER FLUORINE COMPOUNDS

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: OPEN FLAMES AND HIGH TEMPERATURES

SECTION VI. HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: 1,000 PPM

***EFFECTS OF OVEREXPOSURE ***

INGESTION (SWALLOWING): N/A

INHALATION: EXCESSIVE INHALATION CAN PRODUCE DIZZINESS, NAUSEA, AND HEADACHE

SKIN CONTACT: CONCENTRATED SPRAY MAY CAUSE FREEZING OF SKIN AREA

EYE CONTACT: TEMPORARY IRRITATION

• EMERGENCY AND FIRST AID PROCEDURES *

SKIN: WASH WITH SOAP AND WATER

INHALATION: REMOVE TO FRESH AIR LOCATION

EYES: FLUSH WITH PLENTY OF WATER, CALL PHYSICIAN IMMEDIATELY.

SECTION VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: REMOVE LEAKING CONTAINER TO OUTSIDE DISPOSAL SITE.

WASTE DISPOSAL METHOD: EMPTY FULLY, INCLUDING GAS PRESSURE. DO NOT PUNCTURE OR INCINERATE. CAN MAY BE RECYCLED OR ALTERNATIVELY REMOVED TO A SANITARY LANDFILL IN MOST LOCALITIES. CHECK APPLICABLE REGULATIONS.

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED WITH ADEQUATE VENTILATION

VENTILATION: ADEQUATE VENTILATION NEEDED

PROTECTIVE GLOVES: RECOMMENDED BUT NOT REQUIRED

EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS.

OTHER PROTECTIVE EQUIPMENT: AS YOUR COMPANY REQUIRES.

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS AWAY FROM DIRECT SUNLIGHT, BELOW 120°F. DO NOT DROP, PUNCTURE, OR INCINERATE. OTHER PRECAUTIONS: DO NOT SPRAY DIRECTLY INTO FLAME. DO NOT SMOKE WHILE USING PRODUCT. DO NOT SPRAY ON FLOORS. CONTAINS 142b, A SUBSTANCE WHICH CAN HARM PUBLIC HEALTH AND THE ENVIRONMENT BY DESTROYING OZONE IN THE UPPER ATMOSPHERE. DESTRUCTION OF THE OZONE LAYER CAN LEAD TO INCREASED ULTRAVIOLET RADIATION WHICH, WITH EXCESSIVE EXPOSURE TO SUNLIGHT, CAN CAUSE AN INCREASE IN SKIN CANCER AND EYE CATARACTS.

SECTION X. CARCINOGENIC HAZARD

NO COMPONENT IN THIS PRODUCT HAS BEEN LISTED AS A CARCINOGEN BY IARC, N.T.P., OSHA, OR ACGIH.

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE CONSULTED IN PREPARING THIS M.S.D.S.

<http://www.slideproducts.com/mold.htm>