

MATERIAL SAFETY DATA SHEET

SLIDE PRODUCTS, INC.  
430 S. WHEELING ROAD  
WHEELING, IL 60090

PRODUCT NAME: SLIDE SILICONE REMOVER

EMERGENCY TELEPHONE: 800-535-5053  
INFORMATON TELEPHONE: 847-541-7220  
FAX NUMBER: 847-541-7986  
PREPARED BY: JIM ARMSTRONG

REVISION DATE: 9-1-06  
PRODUCT NUMBER: 43016  
D.U.N.S. NUMBER: 00-299-4168

**\*\* THIS MSDS PERTAINS TO BOTH 43016(PINTS) AS WELL AS 43001(05) – (GALLONS) \*\***

**SECTION I. IDENTIFICATION**

---

CHEMICAL NAME: NON-IONIC SURFACTANT- POLY (oxyethylene/oxypropylene) GLYCOL  
CHEMICAL FAMILY: ALIPHATIC HC DERIVATIVE  
FORMULA: 43016  
SYNONYMS:  
DOT HAZARD CLASSIFICATION: NON-HAZARDOUS LIQUID  
DOT SHIPPING NAME: NONE NEEDED  
CHEMICAL ABSTRACT REGISTRY NUMBER: PROPRIETARY BLEND  
IDENTIFICATION NUMBER: NONE  
H.M.I.S. RATING: 1,0,0,A

**SECTION II. PHYSICAL DATA**

---

BOILING POINT: NOT ESTABLISHED  
FREEZING POINT: 15 DEGREES F.  
SPECIFIC GRAVITY (H2O =1): 1.03  
WEIGHT PER GALLON @ 60 F.: 8.59  
VAPOR PRESSURE @ 70 f. (MM HG): NOT ESTABLISHED  
VAPOR DENSITY (AIR = 1): PRODUCT IS NON VOLATILE  
PERCENT VOLATILE BY VOLUME: 0  
EVAPORATION RATE (MINUTES): N/A  
APPEARANCE AND ODOR: CLEAR LIQUID, SLIGHT SURFACTANT ODOR

**SECTION III. HAZARDOUS INGREDIENTS**

---

MATERIAL:	APPROX. VOLUME %:	TLV(UNITS):
NO KNOWN HAZARDOUS MATERIALS PRESENT		
**CONTAINS NO OZONE DEPLETING CHEMICALS**		

**SECTION IV. FIRE AND EXPLOSION HAZARD DATA**

---

FLAMMABLE LIMITS IN AIR: LEL: N/A UEL: N/A (VOLUME %)  
FLASH POINT: 250 DEGREES F.  
EXTINGUISHING MEDIA: A,B,C, ALL CLASS POWDER  
SPECIAL FIRE FIGHTING PROCEDURES: NONE  
UNUSUAL FIRE & EXPLOSION HAZARDS: NONE

**SECTION V. REACTIVITY DATA**

---

STABILITY: STABLE  
INCOMPATIBILITY (MATERIALS TO AVOID): STRONG OXIDIZING AGENTS  
HAZARDOUS COMBUSTION BY-PRODUCTS:  
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR  
CONDITIONS TO AVOID: NONE

---

**SECTION VI. HEALTH HAZARD DATA**

---

THRESHOLD LIMIT VALUE: NOT ESTABLISHED

• **EFFECTS OF OVEREXPOSURE \***

INHALATION: N/A  
SKIN CONTACT: MAY CAUSE IRRITATION  
EYE CONTACT: TEMPORARY IRRITANT

• **EMERGENCY AND FIRST AID PROCEDURES \***

SKIN: WASH WITH SOAP AND WATER, APPLY HAND CREAM  
INHALATION: N/A  
EYES: WASH THOROUGHLY WITH COLD CLEAN WATER FOR 15 MINUTES  
CONSULT PHYSICIAN IMMEDIATELY IF IRRITATION PERSISTS.

---

**SECTION VII. SPILL OR LEAK PROCEDURES**

---

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: USE ABSORBENT COMPOUND TO REMOVE OR FLUSH INTO SEWER AS PERMITTED  
WASTE DISPOSAL METHOD: INCINERATE OR LANDFILL AS PERMITTED BY LOCAL, STATE OR FEDERAL REGULATIONS.

---

**SECTION VIII. SPECIAL PROTECTION INFORMATION**

---

RESPIRATORY PROTECTION (SPECIFY TYPE): NOT NEEDED  
VENTILATION: N/A  
PROTECTIVE GLOVES: MAY BE USED  
EYE PROTECTION: PROPER EYE CARE SHOULD BE PRACTICED IN ALL INDUSTRIAL OPERATIONS.  
OTHER PROTECTIVE EQUIPMENT: AS REQUIRED BY YOUR COMPANY

---

**SECTION IX. SPECIAL PRECAUTIONS**

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE INDOORS, AVOID FREEZING.  
STORE AT TEMPERATURES BELOW 120° F.  
OTHER PRECAUTIONS: NONE

---

THIS DATA IS OFFERED IN GOOD FAITH AT TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EXPRESS OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE, AND DETERMINE WHETHER THEY ARE APPROPRIATE. THE INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET IS BELIEVED TO BE CORRECT AS OF THIS DATE. THE REGULATIONS PROMULGATED BY OSHA FOR HAZARD COMMUNICATION, 29 CFR 1910.1200, AS WELL AS SEVERAL STATE AND LOCAL LAWS AND REGULATIONS, HAVE BEEN CONSULTED IN PREPARING THIS M.S.D.S.

<http://www.slideproducts.com/cleaners.htm>