TECHNICAL DATA SHEET

Heavy-Duty 10% Mold Release Bulk/Liquid
54901HB, 54905HB, 54955HB

Product Description	Heavy-Duty 10% Mold Release provides Slide's highest percentage of active ingredients for a release agent. It is also widely used in conjunction with Slide's Super Grease Ejector Pin Grease on ejector pins. It's an ideal lubricant for the front half of ejector pins (pins in forward position). This product acts as a nearly dry lubricant minimizing the possibility of leaching out onto molded parts. Food-approved formulation that is paintable and non-silicone.
Applications	Mold Release
Unit Package Description	1, 5 and 55-gallon containers
Generic Description	Mold Release
Approx. Net Weight Fill per Gal.	7 pounds
Net Weight Fill	1 - 55 gallons
Appearance	Clear Oily Colorless Liquid
Odor	Mild, Petroleum like
Flash Point F	25 degrees
Flash Point C	Negative 4 degrees
Base Type	Propylene Glycol
Evaporation Rate	Fast
HMIS Rating	2, 3, 0, X
DOT Proper Shipping Name	UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II
VOC % (Federal)	90
VOC g/L (Federal)	654.92
VOC lbs./Gal (Federal)	5.46
Removal	Remove with organic or hydrocarbon solvents
Food Safety Citation (CFR)	21CFR 178.3570
Units Per Case	1
Case Weight (lbs)	Various
Working Temperature F	32 to 450 degrees
Working Temperature C	0 to 232 degrees
Specific Gravity	0.791