

1. Identification

Product identifier 40810PC

Product Identity Slide Econo-Spray 3 Food Approved Mold Release **Other means of identification** Econo-Spray 3 Food Approved Mold Release, 40810P

Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Release

Details of the supplier of the safety data sheet

Company Name Slide Products Inc.

430 Wheeling Road Wheeling, IL 60090

Initial supplier identifier

THIS SAFETY DATA SHEET IS NOT COMPLIANT UNLESS CANADIAN

ADDRESS IS USED

PLEASE CONTACT A CANADIAN SLIDE DISTRIBUTOR FOR THE FULLY

COMPLIANT SDS FILE

Emergency

24 hour Emergency Emergency Telephone INFOTRAC 1-352-323-3500 (International)

Telephone No. 1-800-535-5053 (North America)

Customer Service: Phone: 1-847-541-7220

Fax: 1-847-541-7986

2. Hazard(s) identification

Classification of the substance or mixture

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.



Label elements









Danger

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

May cause drowsiness and dizziness.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

[Prevention]:

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Keep container tightly closed.

Avoid breathing dust, fume, gas, mist, vapours, spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves, eye protection, and face protection.

[Response]:

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER, doctor or physician if you feel unwell.

If skin irritation occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

Leaking gas fire - do not extinguish unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

Collect spillage.

[Storage]:

Store in a well ventilated place. Keep container tightly closed.

Store in a well ventilated place. Keep cool.

Store locked up.

Protect from sunlight. Store in a well ventilated place.

[Disposal]:

Dispose of contents or container in accordance with local and national regulations.



3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Heptane	45 - 70	Flam. Liq. 2;H225	
CAS Number: 0000142-82-5		Asp. Tox. 1;H304	
Synonyms: Heptane		Skin Irrit. 2;H315	
		STOT SE 3;H336	
		Aquatic Acute 1;H400	
		Aquatic Chronic 1;H410	
Petroleum gases, liquefied	30 - 60	Press. Gas;H280	
CAS Number: 0068476-86-8		Flam. Gas 1;H220	
Synonyms: Petroleum gases, liquefied, sweetened			
Polypropylene glycol, monobutyl ether	7 - 13	Not Classified	
CAS Number: 0009003-13-8			
Synonyms: Polypropylene glycol monobutyl ether			

The actual concentration or concentration range is withheld as a trade secret.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or

stopped, give artificial respiration. If unconscious, place in the recovery position and

obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart

and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce

vomiting.

^{*}PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.



Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation May cause drowsiness or dizziness.

Skin	Causes skin irritation.
	Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Keep container tightly closed.

Avoid breathing dust, fume, gas, mist, vapours, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids. See section 2 for further details. - [Storage]:

Specific end use(s)

No available information



Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000142-82-5	Heptane	ACGIH	TWA: 400 ppm STEL: 500
	100 7111 1610 / 37111 500 6751 0050 / 36751		ppm
Alberta	400 ppm TWA; 1640 mg/m³TWA 500 ppm STEL; 2050 mg/m³STEL		
British Columbia	400 ppm TWA 500 ppm STEL		
	TO PER TO SERVICE STATE OF THE		
Manitoba	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under		
	Heptane, all isomers)		
New Brunswick	400 ppm TWA; 1640 mg/m³TWA 500 ppm STEL; 2050 mg/m³STEL		
Newfoundland and	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under		
Labrador	Heptane, all isomers)		
Nova Scotia	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)		
Northwest Territories	400 ppm TWA 500 ppm STEL		
	TO PER TO SERVICE STATE OF THE		
Nunavut	400 ppm TWA 500 ppm STEL		
Ontario	400 ppm TWA 500 ppm STEL (listed under Heptane, all isomers)		
Prince Edward Island	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under		
	Heptane, all isomers)		
Quebec	400 ppm TWAEV; 1640 mg/m³TWAEV 500 ppm STEV; 2050 mg/m³ STEV		
Saskatchewan	400 ppm TWA 500 ppm STEL		
Yukon	400 ppm TWA; 1600 mg/m³TWA 500 ppm STEL; 2000 mg/m³STEL		
0000003.43.0	Delayer has also described to the control of the co	466111	No established their
0009003-13-8 Alberta	Polypropylene glycol, monobutyl ether No Established Limit	ACGIH	No Established Limit
Alberta	No Established Limit		
British Columbia	No Established Limit		
Manitoba	No Established Limit		
IVIAIIILODA	No Established Limit		
New Brunswick	No Established Limit		
Newfoundland and	No Established Limit		
Labrador	INO ESTABILISTICO ETITIL		
Nova Scotia	No Established Limit		
Northwest Territories	No Established Limit		



CAS No.	Ingredient	Source Value
Nunavut	No Established Limit	,
Ontario	No Established Limit	
Prince Edward Island	No Established Limit	
	N. 5 . 10 1 . 11 . 11	
Quebec	No Established Limit	
Saskatchewan	No Established Limit	
Yukon	No Established Limit	
0068476-86-8	Petroleum gases, liquefied	ACGIH No Established Limit
Alberta	No Established Limit	
British Columbia	No Established Limit	
British columbia	100 Established Elline	
Manitoba	No Established Limit	
New Brunswick	No Established Limit	
Newfoundland and Labrador	No Established Limit	
	No Established Limit	
Nova Scotia	NO Established Limit	
Northwest Territories	No Established Limit	
Nunavut	No Established Limit	
Ontario	No Established Limit	
Prince Edward Island	No Established Limit	
Quebec	No Established Limit	
Saskatchewan	No Established Limit	
Yukon	No Established Limit	

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use

the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Wear PVC or rubber gloves to keep skin contact to a

minimum. Refer to the manufacturer's recommendations regarding the suitability

of any gloves used.



Engineering Provide adequate ventilation. Where reasonably practicable this should be Controls achieved by the use of local exhaust ventilation and good general extraction. If

these are not sufficient to maintain concentrations of particulates and any vapour

below occupational exposure limits suitable respiratory protection must be worn.

Other Work Use good personal hygiene practices. Wash hands before eating, drinking, **Practices**

smoking or using toilet. Promptly remove soiled clothing and wash thoroughly

before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance Clear Pressurized aerosol dispensed as a mist.

Odour Not Available

Odour threshold No available information No available information рΗ Melting point / freezing point No available information

Initial boiling point and boiling range 70 °C / 159 °F **Flash Point** Not available Faster than ether **Evapouration rate (Ether = 1)**

Flammability (solid, gas) Gas

Upper/lower flammability or explosive limits Lower Explosive Limit: 7.5 %

Upper Explosive Limit: 1.2 %

Vapour pressure (Pa) 137 mm Hg **Vapour Density** Heavier than air

Relative Density 0.6288

Solubility in Water No available information Partition coefficient n-octanol/water (Log Kow) No available information **Auto-ignition temperature** No available information **Decomposition temperature** No available information No available information Viscosity (cSt) **Oxidising properties** No available information **Explosive properties** No available information

Other information

No other relevant information.



Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong oxidizing agents and acids.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

	Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
He	eptane - (142-82-5)					



Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Petroleum gases, liquefied - (68476-86-8)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Polypropylene glycol, monobutyl ether - (9003-13-8)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000142-82-5	Heptane	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	No Established Limit		
0009003-13-8	Polypropylene glycol, monobutyl ether	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	No Established Limit		
0068476-86-8	Petroleum gases, liquefied	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
	No Established Limit	ii ii c	Group 1. No, Group 20. No, Group 20. No, Group 1. No,

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Symptoms and effects, both acute and delayed::

Treat symptomatically.

Inhalation May cause drowsiness or dizziness.

Skin Causes skin irritation.



Section 12. Ecological information

Toxicity

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Heptane - (142-82-5)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Petroleum gases, liquefied - (68476-86-8)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Polypropylene glycol, monobutyl ether - (9003-13-8)	{CalcFish}	{CalcCrust}	{CalcAlgae}

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1 - 2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface	ICAO/IATA	
	Transportation)	Transportation)	
UN number	UN1950	UN1950	UN1950
UN proper	UN1950, Aerosols	Aerosols, Flammable, (each	Aerosols, Flammable,
shipping		not exceeding 1 L capacity)	(each not exceeding 1 L
name		(Heptane)	capacity) (Heptane)
Transport	TDG Hazard Class: 2.1	IMDG:2.1	Air Class:2.1
hazard	Sub Class:Not	Sub Class:Not Applicable	Sub Class: Not Applicable
class(es)	Applicable		
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

Marine Pollutant: Yes; (Heptane)

Special precautions for user

No available information



Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

NFPA Health Hazards Flammability Instability Special Hazards
Not determined Not determined Not determined

Canadian Domestic Substance List (DSL):

Heptane

Petroleum gases, liquefied

Polypropylene glycol, monobutyl ether

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



Section 16. Other information

SDS Revision Date 11/02/2023

HMIS Health Hazards Flammability Physical Hazards Personal Protection 1 4 0 B

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness and dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

End of Document