



## Section 1. Identification

**Product identifier** 417BULK

**Product Identity** Slide Dura Kote Mold Release Bulk

**Other means of identification** Slide Dura Kote Mold Release Bulk  
( SDS applies to pint, 1G, 5G, and 55G sizes )

### Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Release

### Details of the supplier of the safety data sheet

**Company Name** Slide Products Inc.  
430 Wheeling Road  
Wheeling, IL 60090

**Initial Supplier Identifier:** THIS SAFETY DATA SHEET IS NOT COMPLIANT UNLESS  
CANADIAN ADDRESS IS USED  
PLEASE CONTACT A CANADIAN SLIDE DISTRIBUTOR FOR THE  
FULLY COMPLIANT SDS FILE

### Emergency

**24 hour Emergency Telephone No.** Emergency Telephone INFOTRAC 1-352-323-3500  
(International)  
1-800-535-5053 (North America)

**Customer Service:** Phone: 1-847-541-7220  
Fax: 1-847-541-7986

## Section 2. Hazard(s) identification

### Classification of the substance or mixture

Causes skin irritation.

Causes serious eye irritation.

Causes damage to organs through prolonged or repeated exposure. Specific Target

Organs: (central nervous system hearing organs)

Very toxic to aquatic life with long lasting effects.

**Label elements****Danger**

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness and dizziness.

Causes damage to organs through prolonged or repeated exposure.

Very toxic to aquatic life with long lasting effects.

**[Prevention]:**

Keep container tightly closed.

Do not breathe dust, fume, mist, vapours or spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves, eye protection, and face protection.

**[Response]:**

IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER, doctor or physician if you feel unwell.

Get Medical advice or attention if you feel unwell.

Do NOT induce vomiting.

If skin irritation occurs: Get medical attention.

If eye irritation persists: Get medical advice or attention.

Take off contaminated clothing and wash it before reuse.

Collect spillage.

**[Storage]:**

Store in a well ventilated place. Keep container tightly closed.

Store locked up.

**[Disposal]:**

Dispose of contents or container in accordance with local and national regulations.

### Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Heptane CAS Number: 142-82-5 Synonyms: n-Heptane	30 - 60	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 1;H410	----
Isopropyl Alcohol CAS Number: 67-63-0 Synonyms: ISOPROPANOL, Propan-2-ol, ISOPROPYL ALCOHOL (manufacture-strong acid process, Solvent C-3	30 - 60	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	----
Stoddard solvent CAS Number: 8052-41-3 Synonyms: White spirits	3 - 4	STOT RE 1;H372 Asp. Tox. 1;H304	----
Benzene, ethylmethyl- CAS Number: 25550-14-5 Synonyms: No available information	0.1 - 1		----
Benzene, trimethyl- CAS Number: 25551-13-7 Synonyms: Trimethylbenzene, Trimetyl benzene, Trimetilbenzena, Trimethyl benzene	0.1 - 1	Acute Tox. 4;H302 Acute Tox. 4;H312 Skin Irrit. 2;H315 Flam. Liq. 3;H226 Eye Irrit. 2;H319	----
Ethylbenzene CAS Number: 100-41-4 Synonyms: Etylbenzen, Benzene, ethyl-, Ethyl Benzene	0.5 - 1	Flam. Liq. 2;H225 Acute Tox. 4;H332 STOT RE 2;H373 Asp. Tox. 1;H304 Aquatic Chronic 3;H412	----
Xylene CAS Number: 1330-20-7 Synonyms: No available information	1 - 3	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	----

The actual concentration or concentration range is withheld as a trade secret.

\*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

## Section 4. First aid measures

### Description of first aid measures

- General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### Most important symptoms and effects, both acute and delayed

**Overview** No chronic toxicity or long term toxicity information available. Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

- Eyes** Causes serious eye irritation.
- Skin** Causes skin irritation.

## Section 5. Fire-fighting measures

### Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Unsuitable extinguishing media: Do not use; water jet.

### Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep container tightly closed.

Do not breathe dust, fume, mist, vapours or spray.

Do not get in eyes, on skin, or on clothing.

### Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### Environmental precautions

Do not allow spills to enter drains or waterways.

### Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

## Section 7. Handling and storage

### Precautions for safe handling

Handle containers carefully to prevent damage and spillage.  
 See section 2 for further details. - [Prevention]:

### Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids.  
 See section 2 for further details. - [Storage]:

### Specific end use(s)

No available information

## Section 8. Exposure controls / personal protection

### Control parameters

#### Exposure Limits

CAS No.	Ingredient	Source	Value
67-63-0	Isopropyl Alcohol	ACGIH	200 ppm 400 ppm
		Alberta	200 ppm TWA; 492 mg/m <sup>3</sup> TWA 400 ppm STEL; 984 mg/m <sup>3</sup> STEL
		British Columbia	200 ppm TWA 400 ppm STEL
		Manitoba	200 ppm TWA 400 ppm STEL
		New Brunswick	400 ppm TWA; 983 mg/m <sup>3</sup> TWA 500 ppm STEL; 1230 mg/m <sup>3</sup> STEL
		Newfoundland and Labrador	200 ppm TWA 400 ppm STEL
		Nova Scotia	200 ppm TWA 400 ppm STEL
		Northwest Territories	200 ppm TWA 400 ppm STEL
		Nunavut	200 ppm TWA 400 ppm STEL
		Ontario	200 ppm TWA 400 ppm STEL
		Prince Edward Island	200 ppm TWA 400 ppm STEL
		Quebec	400 ppm TWAEV; 985 mg/m <sup>3</sup> TWAEV 500 ppm STEV; 1230 mg/m <sup>3</sup> STEV
		Saskatchewan	200 ppm TWA 400 ppm STEL
		Yukon	400 ppm TWA; 980 mg/m <sup>3</sup> TWA 500 ppm STEL; 1225 mg/m <sup>3</sup> STEL
100-41-4	Ethylbenzene	ACGIH	20 ppm
		Alberta	100 ppm TWA; 434 mg/m <sup>3</sup> TWA 125 ppm STEL; 543 mg/m <sup>3</sup> STEL
		British Columbia	20 ppm TWA
		Manitoba	20 ppm TWA
		New Brunswick	100 ppm TWA; 434 mg/m <sup>3</sup> TWA 125 ppm STEL; 543 mg/m <sup>3</sup> STEL
		Newfoundland and Labrador	20 ppm TWA
		Nova Scotia	20 ppm TWA
		Northwest Territories	100 ppm TWA 125 ppm STEL
		Nunavut	100 ppm TWA 125 ppm STEL
		Ontario	20 ppm TWA
		Prince Edward Island	20 ppm TWA
		Quebec	100 ppm TWAEV; 434 mg/m <sup>3</sup> TWAEV 125 ppm STEV; 543 mg/m <sup>3</sup> STEV



**Safety Data Sheet**  
**Slide Dura Kote Mold Release Bulk**

**SDS Revision Date: 08/21/2025**

		Saskatchewan	100 ppm TWA 125 ppm STEL
		Yukon	100 ppm TWA; 435 mg/m <sup>3</sup> TWA 125 ppm STEL; 545 mg/m <sup>3</sup> STEL
142-82-5	Heptane	ACGIH	200 ppm 400 ppm
		Alberta	400 ppm TWA; 1640 mg/m <sup>3</sup> TWA 500 ppm STEL; 2050 mg/m <sup>3</sup> STEL
		British Columbia	400 ppm TWA 500 ppm STEL
		Manitoba	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		New Brunswick	400 ppm TWA; 1640 mg/m <sup>3</sup> TWA 500 ppm STEL; 2050 mg/m <sup>3</sup> STEL
		Newfoundland and Labrador	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		Nova Scotia	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		Northwest Territories	400 ppm TWA 500 ppm STEL
		Nunavut	400 ppm TWA 500 ppm STEL
		Ontario	400 ppm TWA 500 ppm STEL (listed under Heptane, all isomers)
		Prince Edward Island	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		Quebec	400 ppm TWAEV; 1640 mg/m <sup>3</sup> TWAEV 500 ppm STEV; 2050 mg/m <sup>3</sup> STEV
		Saskatchewan	400 ppm TWA 500 ppm STEL
		Yukon	400 ppm TWA; 1600 mg/m <sup>3</sup> TWA 500 ppm STEL; 2000 mg/m <sup>3</sup> STEL
1330-20-7	Xylene	ACGIH	TWA: 100 ppm STEL: 150 ppm
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
8052-41-3	Stoddard solvent	ACGIH	100 ppm
		Alberta	100 ppm TWA; 572 mg/m <sup>3</sup> TWA
		British Columbia	290 mg/m <sup>3</sup> TWA 580 mg/m <sup>3</sup> STEL
		Manitoba	100 ppm TWA
		New Brunswick	100 ppm TWA; 525 mg/m <sup>3</sup> TWA
		Newfoundland and Labrador	100 ppm TWA
		Nova Scotia	100 ppm TWA
		Northwest Territories	100 ppm TWA 125 ppm STEL
		Nunavut	100 ppm TWA 125 ppm STEL
		Ontario	525 mg/m <sup>3</sup> TWA (140C Flash aliphatic solvent)
		Prince Edward Island	100 ppm TWA
		Quebec	100 ppm TWAEV; 525 mg/m <sup>3</sup> TWAEV
		Saskatchewan	100 ppm TWA 125 ppm STEL
		Yukon	100 ppm TWA; 575 mg/m <sup>3</sup> TWA 150 ppm STEL; 720 mg/m <sup>3</sup> STEL
25550-14-5	Benzene, ethylmethyl-	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit

25551-13-7	Benzene, trimethyl-	Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
		ACGIH	10 ppm
		Alberta	25 ppm TWA; 123 mg/m <sup>3</sup> TWA
		British Columbia	25 ppm TWA
		Manitoba	25 ppm TWA
		New Brunswick	25 ppm TWA; 123 mg/m <sup>3</sup> TWA
		Newfoundland and Labrador	25 ppm TWA
		Nova Scotia	25 ppm TWA
		Northwest Territories	25 ppm TWA 30 ppm STEL
		Nunavut	25 ppm TWA 30 ppm STEL
		Ontario	25 ppm TWA
		Prince Edward Island	25 ppm TWA
		Quebec	25 ppm TWAEV; 123 mg/m <sup>3</sup> TWAEV
		Saskatchewan	25 ppm TWA 30 ppm STEL
		Yukon	25 ppm TWA; 120 mg/m <sup>3</sup> TWA 35 ppm STEL; 180 mg/m <sup>3</sup> STEL

## Exposure controls

**Respiratory** If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

**Eyes** Protective safety glasses recommended.

**Skin** Avoid skin contact. Protective gloves recommended.

**Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

**Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.



## Section 9. Physical and chemical properties

<b>Appearance</b>	Liquid
<b>Odour</b>	No available information
<b>Odour threshold</b>	No available information
<b>pH</b>	No available information
<b>Melting point / freezing point</b>	No available information
<b>Initial boiling point and boiling range</b>	No available information
<b>Flash Point</b>	No available information
<b>Evapouration rate (Ether = 1)</b>	No available information
<b>Flammability (solid, gas)</b>	Flammable Liquid
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> No available information <b>Upper Explosive Limit:</b> No available information
<b>Vapour pressure (Pa)</b>	No available information
<b>Vapour Density</b>	No available information
<b>Relative Density</b>	No available information
<b>Solubility in Water</b>	No available information
<b>Partition coefficient n-octanol/water (Log Kow)</b>	No available information
<b>Auto-ignition temperature</b>	No available information
<b>Decomposition temperature</b>	No available information
<b>Viscosity (cSt)</b>	No available information
<b>Oxidising properties</b>	No available information
<b>Explosive properties</b>	No available information
<b>Other information</b>	No other relevant information.

## Section 10. Stability and reactivity

### Reactivity

Hazardous Polymerization will not occur.

### Chemical stability

Stable under normal circumstances.

### Possibility of hazardous reactions

No available information

### Conditions to avoid

Excessive heat and open flame.

### Incompatible materials

Strong oxidizing agents and acids.

### Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

## Section 11. Toxicological information

### Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



**Safety Data Sheet**  
**Slide Dura Kote Mold Release Bulk**

**SDS Revision Date: 08/21/2025**

<b>Ingredient</b>	<b>Oral LD50, mg/kg</b>	<b>Skin LD50, mg/kg</b>	<b>Inhalation vapour LC50, mg/L/4hr</b>	<b>Inhalation Dust/Mist LC50, mg/L/4hr</b>	<b>Inhalation Gas LC50, ppm</b>
Heptane - (142-82-5)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Isopropyl Alcohol - (67-63-0)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Stoddard solvent - (8052-41-3)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Benzene, ethylmethyl- - (25550-14-5)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Benzene, trimethyl- - (25551-13-7)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Ethylbenzene - (100-41-4)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Xylene - (1330-20-7)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}

**Carcinogen Data**

<b>CAS No.</b>	<b>Ingredient</b>	<b>Source</b>	<b>Value</b>
67-63-0	Isopropyl Alcohol	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
		ACGIH	A4
100-41-4	Ethylbenzene	IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
		ACGIH	A3
142-82-5	Heptane	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
1330-20-7	Xylene	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
		ACGIH	No Established Limit
8052-41-3	Stoddard solvent	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
25550-14-5	Benzene, ethylmethyl-	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
25551-13-7	Benzene, trimethyl-	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	A4



**Safety Data Sheet**  
**Slide Dura Kote Mold Release Bulk**

**SDS Revision Date: 08/21/2025**

<b>Classification</b>	<b>Category</b>	<b>Hazard Description</b>
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure	1	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

**Possible routes of entry:** No available information

**Symptoms and effects, both acute and delayed:**

No chronic toxicity or long term toxicity information available. Treat symptomatically.

**Inhalation** May cause drowsiness or dizziness.

**Eyes** Causes serious eye irritation.

**Skin** Causes skin irritation.

## Section 12. Ecological information

### Toxicity

Very toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Heptane - (142-82-5)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Isopropyl Alcohol - (67-63-0)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Stoddard solvent - (8052-41-3)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Benzene, ethylmethyl- - (25550-14-5)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Benzene, trimethyl- - (25551-13-7)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Ethylbenzene - (100-41-4)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Xylene - (1330-20-7)	{CalcFish}	{CalcCrust}	{CalcAlgae}

### Persistence and degradability

There is no data available on the preparation itself.

### Bioaccumulative potential

No available information

### Mobility in soil

No available information

### Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

### Other adverse effects

No available information

## Section 13. Disposal considerations

### Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

### Section 14. Transport information

Not regulated for packages under 5L (1.3 gallons) or 5.0 kg (11 lbs).

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	<b>TDG (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>UN number</b>	UN1993	UN1993	UN1993
<b>UN proper shipping name</b>	Flammable Liquid, n.o.s. (Heptane, Isopropanol)	Flammable Liquid, n.o.s. (Heptane, Isopropanol)	Flammable Liquid, n.o.s. (Heptane, Isopropanol)
<b>Transport hazard class(es)</b>	<b>Class:</b> 3 <b>Sub Class:</b> Not Applicable	<b>Class:</b> 3 <b>Sub Class:</b> Not Applicable	<b>Class:</b> 3 <b>Sub Class:</b> Not Applicable
<b>Packing group</b>	II	II	II

**Environmental hazards**

IMDG Marine Pollutant: Yes; ( Heptane )

**Special precautions for user**

No available information

### Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) and the SDS contains all of the information required by those regulations.

**Canadian Domestic Substance List (DSL):**

Benzene, ethylmethyl-  
 Benzene, trimethyl-  
 Ethylbenzene  
 Heptane  
 Isopropyl Alcohol  
 Stoddard solvent

**Canadian Non-Domestic Substance List (NDSL):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



**Section 16. Other information**

**SDS Revision Date**

08/21/2025

<b><u>NFPA</u></b>	<b>Health Hazards</b> Not determined	<b>Flammability</b> Not determined	<b>Instability</b> Not determined	<b>Special Hazards</b> Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b> 2	<b>Flammability</b> 3	<b>Physical Hazards</b> 0	<b>Personal Protection</b> X

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness and dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

**End of Document**