



Safety Data Sheet

Issue Date: 09-Jan-2012

Revision Date: 01-Jan-2015

Version 2

1. IDENTIFICATION

Product Identifier

Product Name Super Grease Aerosol

Other means of identification

SDS # 43911

Product Code 43911

UN/ID No UN1950

Recommended use of the chemical and restrictions on use

Recommended Use Industrial ejector pin lubricant.

Details of the supplier of the safety data sheet

Supplier Address

Slide Products Inc.
430 S. Wheeling Road
Wheeling, IL 60090

Emergency Telephone Number

Company Phone Number Phone: 1-847-541-7220

Fax: 1-847-541-7986

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Water white liquid

Physical State Aerosol

Odor Sweet ether odor

Classification

Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable Aerosols	Category 2

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word

Danger

Hazard Statements

Causes skin irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Flammable Aerosol

**Precautionary Statements - Prevention**

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation occurs: Get medical advice/attention
 Take off contaminated clothing and wash it before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

Unknown Acute Toxicity

2% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Hexane	110-54-3	50-65
1-decene, Homopolymer, Hydrogenated	68037-01-4	20-30
Propane	68476-86-8	10-20
Mineral Oil	8042-47-5	3-5
Poly(tetrafluoroethylene)	9002-84-0	0.5-1.5
Benzene, Ethynyl-, Polymer with 2-methyl1,3-butadiene, Hydrogenated	68648-89-5	0.5-1.5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	If exposed or concerned: Get medical advice/attention.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing. Wash contaminated clothing before reuse. Get medical attention if irritation occurs.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician if you feel unwell.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Most important symptoms and effects

Symptoms	May cause skin and eye irritation. Ingestion may cause nausea and burning sensation. Long term overexposure may cause liver and kidney damage. Overexposure by inhalation may cause CNS depression- drowsiness, dizziness, confusion or loss of coordination. If product is heated, inhalation of fumes released from product may cause 'polymer fume fever', a flu like illness. Symptoms of 'polymer fume fever' may include fever, chills, headache, nausea and muscle pain. Health effects caused by fluorine, hydrofluoric acid and its mineral salts.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Carbon dioxide (CO₂). Foam. Water.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Aerosols are under pressure. Heat may cause the containers to explode. Combustion products may be toxic.

Hazardous Combustion Products Carbon oxides.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use water spray to keep fire-exposed containers cool. Do not allow run-off from fire-fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protective equipment as required. Refer to protective measures listed in sections 7 and 8. Keep people away from and upwind of spill/leak. Ventilate affected area. Remove all sources of ignition.
Environmental Precautions	Prevent contamination of surface and groundwater. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Use a non-combustible material like vermiculite or sand to soak up the product and place into a container for later disposal. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Wash thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Pressurized container: Do not pierce or burn, even after use. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Do not spray on an open flame or other ignition source. Empty containers may contain flammable vapors/residue. Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
--------------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Do not expose to temperatures exceeding 50 °C/122°F. Protect from sunlight. Inspect containers periodically for defects. Protect container from physical damage.
Incompatible Materials	Oxidizing agents. Reactive metals. Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexane 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³

Appropriate engineering controls

Engineering Controls	Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapor below the OEL, suitable respiratory protection must be worn.
-----------------------------	--

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Wear eye/face protection. Chemical splash goggles.
Skin and Body Protection	Wear suitable gloves. Consult the glove manufacturer for the most appropriate glove material.
Respiratory Protection	In the case of vapor formation, use a respirator with an approved filter. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
General Hygiene Considerations	Do not breathe vapors or spray mist. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Aerosol	Odor	Sweet ether odor
Appearance	Water white liquid	Odor Threshold	Not determined
Color	Water white		

Property	Values	Remarks • Method
pH	No information available	
Melting Point/Freezing Point	< -40 °C / <-40 °F	
Boiling Point/Boiling Range	69 °C / 156 °F	
Flash Point	-22 °C / -7.6 °F	
Evaporation Rate	No information available	
Flammability (Solid, Gas)	Flammable aerosol	
Upper Flammability Limits	7.7%	
Lower Flammability Limit	1.2%	
Vapor Pressure	160 mm Hg	@ 21 °C (70 °F)
Vapor Density	No information available	
Specific Gravity	0.659	
Water Solubility	None	
Solubility in other solvents	Not determined	
Partition Coefficient	No information available	
Auto-ignition Temperature	225 °C / 437 °F	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	No information available	
Explosive Properties	Pressurized container: May burst if heated	
Oxidizing Properties	None known	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization	Hazardous polymerization does not occur.
---------------------------------	--

Conditions to Avoid

Ignition sources. Heat. Avoid direct sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Do not puncture or incinerate cans.

Incompatible Materials

Oxidizing agents. Reactive metals. Bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	May be harmful in contact with skin. Causes skin irritation.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not taste or swallow.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Hexane 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
Mineral Oil 8042-47-5	> 5000 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity	Based on the information provided, this product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.
Reproductive toxicity	Suspected of damaging fertility or the unborn child.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

Unknown Acute Toxicity 2% of the mixture consists of ingredient(s) of unknown toxicity.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Hexane 110-54-3		2.1 - 2.98: 96 h Pimephales promelas mg/L LC50 flow-through		1000: 24 h Daphnia magna mg/L EC50
Mineral Oil 8042-47-5		10000: 96 h Lepomis macrochirus mg/L LC50		

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Propane 68476-86-8	<=2.8
Mineral Oil 8042-47-5	6

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Hexane 110-54-3	Toxic Ignitable

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances. **Based on package size, product may be eligible for limited quantity exception.**

DOT

UN/ID No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1

IATA

UN/ID No	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1

IMDG

UN/ID No	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Marine Pollutant	This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Hexane	Present	X		Present		Present	X	Present	X	X
1-decene, Homopolymer, Hydrogenated	Present	X				Present	X	Present	X	X
Propane	Present	X		Present			X	Present	X	X
Mineral Oil	Present	X		Present		Present	X	Present	X	X
Poly(tetrafluoroethylene)	Present	X				Present	X	Present	X	X
Benzene, Ethynyl-, Polymer with 2-methyl1,3-butadiene, Hydrogenated	Present	X				Present	X	Present	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Hexane - 110-54-3	110-54-3	56	1.0

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Hexane 110-54-3	X	X	X
Poly(tetrafluoroethylene) 9002-84-0			X

16. OTHER INFORMATION**NFPA****Health Hazards****Flammability****Instability****Special Hazards**

Not determined

Not determined

Not determined

Not determined

HMIS**Health Hazards****Flammability****Physical Hazards****Personal Protection**

Not determined

Not determined

Not determined

Not determined

Issue Date: 09-Jan-2012
Revision Date: 01-Jan-2015
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet