

Section 1. Identification				
Product identifier	440PBULK			
Product Identity Other means of identificat	Slide Acid Vapour Neutralizer Bulk ion Slide Acid Vapour Neutralizer Bulk (SDS applies to pint, 1G, 5G, and 55G sizes)			
Relevant identified uses of	the substance or mixture and uses advised against			
	Industrial Rust Preventive			
Details of the supplier of the	he safety data sheet			
Company Name	Slide Products Inc. 430 Wheeling Road Wheeling, IL 60090			
Initial Supplier Identifier:	THIS SAFETY DATA SHEET IS NOT COMPLIANT UNLESS CANADIAN ADDRESS IS USED PLEASE CONTACT A CANADIAN SLIDE DISTRIBUTOR FOR THE FULLY COMPLIANT SDS FILE			
Emergency 24 hour Emergency Telephone No. Customer Service:	Emergency Telephone INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America) Phone: 1-847-541-7220 Fax: 1-847-541-7986			

Section 2. Hazard(s) identification

Classification of the substance or mixture

Highly Flammable liquid and vapour. Causes skin irritation. May cause cancer. Harmful to aquatic life. Very toxic to aquatic life with long lasting effects.



Label elements



Danger

Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness and dizziness. May cause cancer. Harmful to aquatic life. Very toxic to aquatic life with long lasting effects.

[Prevention]:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking.

Keep container tightly closed.

Keep cool.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Avoid breathing dust, fume, gas, mist, vapours, spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves, eye protection, and face protection.

[Response]:

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice or attention.

Call a POISON CENTER, doctor or physician if you feel unwell.

If skin irritation occurs: Get medical attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use extinguishing media listed in section 5 of SDS for extinction. Collect spillage.



[Storage]:

Store in a well ventilated place. Keep container tightly closed.

Store in a well ventilated place. Keep cool.

Store locked up.

[Disposal]:

Dispose of contents or container in accordance with local and national regulations.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Heptane	60 - 80	Flam. Liq. 2;H225	
CAS Number: 142-82-5		Asp. Tox. 1;H304	
Synonyms: n-Heptane		Skin Irrit. 2;H315	
		STOT SE 3;H336	
		Aquatic Chronic 1;H410	
Sulfonic acids, petroleum, calcium salts, overbased	1 - 15	Aquatic Chronic 4;H413	
CAS Number: 68783-96-0			
Synonyms: Sulfonic acids, petroluem, calcium salts, and overbase			
Petroleum distillates (naphtha)	1 - 15	Carc. 1B;H350	
CAS Number: 8002-05-9		Skin Irrit. 2;H315	
Synonyms: PETROLEUM DISTILLATES, n.o.s.		Aquatic Acute 2;H401	
		Aquatic Chronic 2;H411	
Lecithin	1 - 5	Not Classified	
CAS Number: 8002-43-5			
Synonyms: No available information			
Distillates (petroleum), solvent refined heavy paraffinic	1 - 5	Not Classified	
CAS Number: 64741-88-4			
Synonyms: Distillates (petroleum), solvent-refined heavy paraffinic;			
Baseoil-unspecified, SEVERELY SOLVENT REFINED HEAVY PARAFFINIC			
PETROLEUM OIL			

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.



Section 4. First aid measures

Description of first aid measures

- **General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- **Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- **Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- **Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- **Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Skin Causes skin irritation.



Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.
Keep away from heat, sparks, open flames, and other ignition sources - No smoking.
Keep container tightly closed.
Keep cool.
Ground, bond container and receiving equipment.
Use explosion-proof electrical, ventilating, light, equipment.
Use only non-sparking tools.
Take action to prevent static discharges.
Avoid breathing dust, fume, gas, mist, vapours, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage. See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids. See section 2 for further details. - [Storage]:

Specific end use(s)

No available information



Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
142-82-5	Heptane	ACGIH	200 ppm 400 ppm
		Alberta	400 ppm TWA; 1640 mg/m ³ TWA 500 ppm STEL; 2050 mg/m ³ STEL
		British Columbia	400 ppm TWA 500 ppm STEL
		Manitoba	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL
			(listed under Heptane, all isomers)
		New Brunswick	400 ppm TWA; 1640 mg/m ³ TWA 500 ppm STEL; 2050 mg/m ³ STEL
		Newfoundland and	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL
		Labrador	(listed under Heptane, all isomers)
		Nova Scotia	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL
			(listed under Heptane, all isomers)
		Northwest Territories	400 ppm TWA 500 ppm STEL
		Nunavut	400 ppm TWA 500 ppm STEL
		Ontario	400 ppm TWA 500 ppm STEL (listed under Heptane, all isomers)
		Prince Edward Island	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL
			(listed under Heptane, all isomers)
		Quebec	400 ppm TWAEV; 1640 mg/m ³ TWAEV 500 ppm STEV; 2050 mg/m ³
			STEV
		Saskatchewan	400 ppm TWA 500 ppm STEL
		Yukon	400 ppm TWA; 1600 mg/m ³ TWA 500 ppm STEL; 2000 mg/m ³ STEL
8002-05-9 Pet	Petroleum distillates (naphtha)	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and	No Established Limit
		Labrador	
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
002-43-5	Lecithin	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and	No Established Limit
		Labrador	
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
54741-88-4		ACGIH	No Established Limit



Safety Data Sheet S Slide Acid vapour Neutralizer Bulk

CAS No.	Ingredient	Source	Value
	Distillates (petroleum), solvent	Alberta	No Established Limit
	refined heavy paraffinic	British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and	No Established Limit
		Labrador	
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
68783-96-0	Sulfonic acids, petroleum, calcium	ACGIH	No Established Limit
	salts, overbased	Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and	No Established Limit
		Labrador	
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³OSHA PEL and 5 mg/m³ACGIH.

Exposure controls

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Avoid skin contact. Wear PVC or rubber gloves to keep skin contact to a minimum. Refer to the manufacturer's recommendations regarding the suitability of any gloves used.
Engineering	Provide adequate ventilation. Where reasonably practicable this should be
Controls	achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.



Safety Data Sheet SDS Revision Date: 07/17/2025 Slide Acid vapour Neutralizer Bulk

Section 9. Physical and chemical properties

Appearance	Liquid
Odour	No available information
Odour threshold	No available information
рН	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	98°C / 208°F
Flash Point	-4°C / 25°F
Evapouration rate (Ether = 1)	No available information
Flammability (solid, gas)	Flammable Liquid
Upper/lower flammability or explosive limits	Lower Explosive Limit: No available
	information
	Upper Explosive Limit: No available
	information
Vapour pressure (Pa)	No available information
Vapour pressure (Pa) Vapour Density	
	No available information
Vapour Density	No available information No available information
Vapour Density Relative Density	No available information No available information No available information
Vapour Density Relative Density Solubility in Water	No available information No available information No available information No available information
Vapour Density Relative Density Solubility in Water Partition coefficient n-octanol/water (Log	No available information No available information No available information No available information
Vapour Density Relative Density Solubility in Water Partition coefficient n-octanol/water (Log Kow)	No available information No available information No available information No available information No available information
Vapour Density Relative Density Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature	No available information No available information No available information No available information No available information
Vapour Density Relative Density Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature Decomposition temperature	No available information No available information No available information No available information No available information No available information
Vapour Density Relative Density Solubility in Water Partition coefficient n-octanol/water (Log Kow) Auto-ignition temperature Decomposition temperature Viscosity (cSt)	No available information No available information

Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)



Section 10. Stability and reactivity

Reactivity Hazardous Polymerization will not occur. Chemical stability Stable under normal circumstances. Possibility of hazardous reactions No available information Conditions to avoid Excessive heat and open flame. Incompatible materials Strong oxidizing agents and acids. Hazardous decomposition products High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



Safety Data Sheet Slide Acid vapour Neutralizer Bulk Safety Data Sheet SDS Revision Date: 07/17/2025

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Heptane - (142-82-5)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Sulfonic acids, petroleum, calcium salts, overbased - (68783-96-0)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Petroleum distillates (naphtha) - (8002-05-9)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Lecithin - (8002-43-5)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Distillates (petroleum), solvent refined heavy paraffinic - (64741-88-4)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}

Carcinogen Data

CAS No.	Ingredient	Source	Value
142-82-5	Heptane	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
8002-05-9	Petroleum distillates (naphtha)	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
		ACGIH	No Established Limit
8002-43-5	Lecithin	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
64741-88-4	Distillates (petroleum),	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
	solvent refined heavy paraffinic	ACGIH	No Established Limit
68783-96-0	Sulfonic acids, petroleum,	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
	calcium salts, overbased	ACGIH	No Established Limit



Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity	1B	May cause cancer.
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Possible routes of entry:

No available information

Symptoms and effects, both acute and delayed:

Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 3 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

Treat symptomatically.

Inhalation May cause drowsiness or dizziness.

Skin Causes skin irritation.



Section 12. Ecological information

Toxicity

Very toxic to aquatic life with long lasting effects. Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Heptane - (142-82-5)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Sulfonic acids, petroleum, calcium salts, overbased - (68783-96-0)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Petroleum distillates (naphtha) - (8002-05-9)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Lecithin - (8002-43-5)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Distillates (petroleum), solvent refined heavy paraffinic - (64741-88-4)	{CalcFish}	{CalcCrust}	{CalcAlgae}

Persistence and degradability

There is no data available on the preparation itself. **Bioaccumulative potential** No available information **Mobility in soil** No available information **Results of PBT and vPvB assessment** This product contains no PBT/vPvB/vPvM chemicals. **Other adverse effects** No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1-2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	icao/iata
UN number	UN1206	UN1206	UN1206
UN proper shipping name	Heptanes Solution	Heptanes Solution	Heptanes Solution
Transport hazard	Class:3	Class:3	Class:3
class(es)	Sub Class:Not Applicable	Sub Class:Not Applicable	Sub Class:Not
class(es) Packing group	Sub Class:Not Applicable	Sub Class: Not Applicable	Sub Class: Not Applicable II
			Applicable

IMDG Marine Pollutant: Yes; (Heptane)

Special precautions for user

No available information



Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

Distillates (petroleum), solvent refined heavy paraffinic

Heptane

Lecithin

Petroleum distillates (naphtha)

Sulfonic acids, petroleum, calcium salts, overbased

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



Section 16. Other information					
SDS Revis	SDS Revision Date 07/17/2025				
<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards	
	Not determined	Not determined	Not determined	Not determined	
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection	
	2	3	0	X	

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness and dizziness.

H350 May cause cancer.

H401 Toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document