



Section 1. Identification

Product identifier 453BULK

Product Identity Zero Film Mold Cleaner
Other means of identification Zero Film Mold Cleaner
(SDS applies to pint, 1G, 5G, and 55G sizes)

Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Cleaner

Details of the supplier of the safety data sheet

Company Name Slide Products Inc.
430 Wheeling Road
Wheeling, IL 60090

Emergency
24 hour Emergency Telephone No. Emergency Telephone INFOTRAC 1-352-323-3500
(International)
1-800-535-5053 (North America)

Customer Service: Phone: 1-847-541-7220
Fax: 1-847-541-7986

Section 2. Hazard(s) identification

Classification of the substance or mixture

Flam. Liq. 2;H225 Highly Flammable liquid and vapour.
Eye Dam. 2A;H319 Causes serious eye irritation.
{PCField5d} May cause drowsiness or dizziness.

Label elements**Danger**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

[Prevention]:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No Smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, light, equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust, fume, gas, mist, vapours, spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection, and face protection.

[Response]:

P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER, doctor or physician if you feel unwell.

P337+313 If eye irritation persists: Get medical advice or attention.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+233 Store in a well ventilated place. Keep container tightly closed.

P403+235 Store in a well ventilated place. Keep cool.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents or container in accordance with local and national regulations.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the NOM-018-STPS-2015 Regulation.

| Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|----------------------------------|----------|--|-------|
| Acetone CAS Number: 67-64-1 | 75 - 100 | Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336 | ---- |

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview No specific symptom data available.

No chronic toxicity or long term toxicity information available. Treat symptomatically. See section 2 for further details.

Eyes Causes serious eye irritation.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.
Keep container tightly closed.
Keep cool.
Ground and bond container and receiving equipment.
Use explosion-proof electrical, ventilating, light, equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Avoid breathing dust, fume, gas, mist, vapours, spray.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet.
Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.
Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite.
Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.
See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: No available information
See section 2 for further details. - [Storage]:

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

| CAS No. | Ingredient | Source | Value |
|---------|------------|--------------------------|---|
| 67-64-1 | Acetone | ACGIH | TWA: 250 ppm STEL: 500 ppm |
| | | DNEL Local Exposure | No Established Limit |
| | | DNEL Systematic Exposure | No Established Limit |
| | | National | 500 ppm TWA VLE-PPT 750 ppm STEL [PPT-CT] |

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.

Skin Avoid skin contact. Protective gloves recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

| | |
|--|---|
| Appearance | Clear Liquid |
| Odor | Typical |
| Odor threshold | No available information |
| pH | No available information |
| Melting point / freezing point | No available information |
| Initial boiling point and boiling range | 133°F / 56.1°C |
| Flash Point | -4°F / -20°C |
| Evaporation rate (Ether = 1) | No available information |
| Flammability (solid, gas) | Flammable Liquid |
| Upper/lower flammability or explosive limits | Lower Explosive Limit: 2.6% Upper Explosive Limit: 12.8% |
| Vapour pressure (Pa) | 186.2 mm Hg (@ 20°C / 68°F) |
| Vapour Density | Heavier than air |
| Relative Density | No available information |
| Solubility in Water | Soluble |
| Partition coefficient n-octanol/water (Log Kow) | No available information |
| Auto-ignition temperature | No available information |
| Decomposition temperature | No available information |
| Viscosity (cSt) | No available information |
| Oxidising properties | No available information |
| Explosive properties | No available information |
| Other information | No other relevant information. |

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Avoid high temperatures and contact with incompatible material

Incompatible materials

No available information

Hazardous decomposition products

No hazardous decomposition data available.

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation vapour LC50, mg/L/4hr | Inhalation Dust/Mist LC50, mg/L/4hr | Inhalation Gas LC50, ppm |
|---------------------|------------------------------|---------------------------------|----------------------------------|-------------------------------------|--------------------------|
| Acetone - (67-64-1) | 5,800.00, Rat - Category: NA | 7,426.00, Rabbit - Category: NA | 76.00, Rat - Category: NA | 50.10, Rat - Category: NA | No data available. |

Carcinogen Data

| CAS No. | Ingredient | Source | Value |
|---------|------------|--------|-------|
| 67-64-1 | Acetone | IARC | No |
| | | ACGIH | A4 |

| Classification | Category | Hazard Description |
|-------------------------------|----------|------------------------------------|
| Acute toxicity (oral) | --- | Not Applicable |
| Acute toxicity (dermal) | --- | Not Applicable |
| Acute toxicity (inhalation) | --- | Not Applicable |
| Skin corrosion/irritation | | |
| Serious eye damage/irritation | 2A | Causes serious eye irritation. |
| Respiratory sensitization | --- | Not Applicable |
| Skin sensitization | --- | Not Applicable |
| Germ cell mutagenicity | --- | Not Applicable |
| Carcinogenicity | --- | Not Applicable |
| Reproductive toxicity | --- | Not Applicable |
| STOT-single exposure | --- | Not Applicable |
| STOT-single exposure | 3 | May cause drowsiness or dizziness. |
| STOT-repeated exposure | --- | Not Applicable |
| Aspiration hazard | --- | Not Applicable |

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

No specific symptom data available.

No chronic toxicity or long term toxicity information available. Treat symptomatically.

Inhalation May cause drowsiness or dizziness.

Eyes Causes serious eye irritation.

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

| Ingredient | 96 hr LC50 fish, mg/L | 48 hr EC50 crustacea, mg/L | ErC50 algae, mg/L |
|---------------------|-------------------------------|----------------------------|---|
| Acetone - (67-64-1) | 8,120.00, Pimephales promelas | 8,800.00, Daphnia pulex | 7,000.00, Pseudokirchneriella subcapitata |

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

| | SCT (Domestic Surface Transportation) | IMO / IMDG (Ocean Transportation) | ICAO/IATA |
|-----------------------------------|--|--|--|
| UN number | UN1090 | UN1090 | UN1090 |
| UN proper shipping name | Acetone | Acetone | Acetone |
| Transport hazard class(es) | Class:3 Sub Class: Not Applicable | Class:3 Sub Class: Not Applicable | Class:3 Sub Class: Not Applicable |
| Packing group | II | II | II |

Environmental hazards

IMDG Marine Pollutant: No;

Special precautions for user

No available information

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria of NOM-018-STPS-2015 and the SDS contains the information required by those regulations.

Mexico - National Inventory of Chemical Substances (INSQ):

Acetone

Section 16. Other information

SDS Revision Date

23 April, 2026

| | | | | |
|--------------------|---|---------------------------------------|--------------------------------------|--|
| <u>NFPA</u> | Health Hazards Not determined | Flammability Not determined | Instability Not determined | Special Hazards Not determined |
| <u>HMIS</u> | Health Hazards 1 | Flammability 3 | Physical Hazards 0 | Personal Protection X |

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document