

SDS Revision Date: 02/02/2024

Section 1. Identification

Product identifier 46370-01-EN

Product IdentitySlide Mold Cleaner WipesOther means of identificationSlide Mold Cleaner Wipes

Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Cleaner.

Details of the supplier of the safety data sheet

Company Name Slide Products Inc.

430 Wheeling Road Wheeling, IL 60090

Initial Supplier Address THIS SAFETY DATA SHEET IS NOT COMPLIANT UNLESS CANADIAN

ADDRESS IS USED

PLEASE CONTACT A CANADIAN SLIDE DISTRIBUTOR FOR THE FULLY

COMPLIANT SDS FILE

Emergency

24 hour Emergency Emergency Telephone INFOTRAC 1-352-323-3500 (International)

Telephone No. 1-800-535-5053 (North America)

Customer Service: Phone: 1-847-541-7220

Fax: 1-847-541-7986

Section 2. Hazard(s) identification

Classification of the substance or mixture

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.



SDS Revision Date: 02/02/2024

Label elements







Warning

Flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

[Prevention]:

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Keep container tightly closed.

Keep cool.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Do not breathe dust, fume, mist, vapours or spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves, eye protection, and face protection.



SDS Revision Date: 02/02/2024

[Response]:

IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Do NOT induce vomiting.

If skin irritation or a rash occurs: Get medical advice or attention.

If eye irritation persists: Get medical advice or attention. Take off contaminated clothing and wash it before reuse.

In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

Collect spillage.

[Storage]:

Store in a well ventilated place. Keep cool.

[Disposal]:

Dispose of contents or container in accordance with local and national regulations.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
1-Propoxy-2-propanol	30 - 60	Flam. Liq. 3;H226	
CAS Number: 1569-01-3		Eye Dam. 2A;H319	
Synonyms: 2-Propanol, 1-propoxy-			

The actual concentration or concentration range is withheld as a trade secret.

^{*}PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.



SDS Revision Date: 02/02/2024

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or

stopped, give artificial respiration. If unconscious, place in the recovery position and

obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart

and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce

vomiting.

Most important symptoms and effects, both acute and delayed

Overview POTENTIAL HEALTH EFFECTS

Eye Contact: May cause tearing, stinging, redness, irritation, and burns.

Inhalation:Irritating to respiratory tract. Prolonged or repeated breathing of very high vapour concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

Ingestion:Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

Skin Contact:Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This

product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

Signs And Symptoms Of Exposure:Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapours can cause effects to liver and kidneys.

Treat symptomatically. Exposure to solvent vapour concentrations from the



component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

SDS Revision Date: 02/02/2024

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Eyes Causes serious eye irritation.

Skin May cause an allergic skin reaction. Causes skin irritation.

Section 5. Fire-fighting measures

Extinguishing media

Use dry chemicals, carbon dioxide foam, water fog, or inert gas (nitrogen) for small fires. For large fires use foam, water fog, or water spray. Water fog and spray are effective in cooling containers and adjacent structures but might cause frothing and/or not achieve extinguishment. A water jet may be used to cool the container's external walls to prevent pressure build-up, auto ignition, or explosion. NEVER use a water jet directly on the fire. Product will float and can be re-ignited on surface of water.

Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Keep container tightly closed.

Keep cool.

Ground, bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use only non-sparking tools.

Take action to prevent static discharges.

Do not breathe dust, fume, mist, vapours or spray.

Do not get in eyes, on skin, or on clothing.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.



SDS Revision Date: 02/02/2024

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. Eliminate ignition sources. Soak up with noncombustible absorbent material. Remove absorbent material for proper disposal.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

See section 2 for further details. - [Prevention]:

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong acids, alkalis, and oxidizers such as liquid chlorine, halogens, hydrogen peroxide, oxygen.

Other Precautions: All labeled precautions must be observed when handling, storing and transporting empty containers due to product residues. Do not reuse containers. Empty containers may contain material residues which can ignite with explosive force. Cutting or welding of empty containers can cause fire, explosion, or release fumes from residues. Keep containers closed and drum bungs in place. Dispose of in a licensed facility.

See section 2 for further details. - [Storage]:

Specific end use(s)

No available information



SDS Revision Date: 02/02/2024

Section 8. Exposure controls / personal protection

Control parameters

Exposure

CAS No.	Ingredient	Source	Value	
1569-01-3	1-Propoxy-2-propanol	ACGIH	No Established Limit	
Alberta	No Established Limit			
British Columbia	No Established Limit			
Manitoba	No Established Limit			
New Brunswick	No Established Limit			
Newfoundland and Labrador	No Established Limit			
Nova Scotia	No Established Limit			
Northwest Territories	No Established Limit			
Nunavut	No Established Limit			
Ontario	No Established Limit			
Prince Edward Island	No Established Limit			
Quebec	No Established Limit			
Saskatchewan	No Established Limit			
Yukon	No Established Limit			

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate,

certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Wear nitrile or similar chemical resistant gloves to keep skin contact to a

minimum.

Refer to the manufacturer's recommendations regarding the suitability of any gloves used.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain

concentrations of particulates and any vapour below occupational exposure limits suitable

respiratory protection must be worn.

Other Work Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet.

Practices Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.



SDS Revision Date: 02/02/2024

Section 9. Physical and chemical properties

Appearance Clear, Colorless Solid containing colorless liquid

Odour Mild

Odour thresholdNo available informationpHNo available information

Melting point / freezing point $< -45 \,^{\circ}\text{C} / < -50 \,^{\circ}\text{F}$ Initial boiling point and boiling range $> 151 \,^{\circ}\text{C} / 305 \,^{\circ}\text{F}$ Flash Point $+ 40 \,^{\circ}\text{C} / 105 \,^{\circ}\text{F}$

Evapouration rate (Ether = 1) <1

Flammability (solid, gas) No available information

Upper/lower flammability or explosive limits Lower Explosive Limit: No available

information

Upper Explosive Limit: No available

information

Vapour pressure (Pa) <2 mmHg @ 70°F Vapour Density >1 (Air= 1) Relative Density 0.8 (Water= 1)

Solubility in Water

No available information

Partition coefficient n-octanol/water (Log

No available information

Kow)

Auto-ignition temperatureNo available informationDecomposition temperatureNo available informationViscosity (cSt)No available informationOxidising propertiesNo available informationExplosive propertiesNo available information

water solubility 1 %

Bulk Density 6.59 lb/gal @ 60 °F

Other information

No other relevant information.



SDS Revision Date: 02/02/2024

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

Excessive heat and open flame.

Incompatible materials

Strong acids, alkalis, and oxidizers such as liquid chlorine, halogens, hydrogen peroxide, oxygen.

Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
1-Propoxy-2-propanol - (1569-01-3)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}



SDS Revision Date: 02/02/2024

Carcinogen Data

CAS No.	Ingredient	Source	Value
1569-01-3	1-Propoxy-2-propanol	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
ACGIH	No Established Limit		

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization		Not Applicable
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable

Symptoms and effects, both acute and delayed::

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause tearing, stinging, redness, irritation, and burns.

Inhalation:Irritating to respiratory tract. Prolonged or repeated breathing of very high vapour concentrations cause euphoria, excitation, and dizziness, headaches, nausea, and vomiting, abdominal pain, fatigue, muscular weakness. Aspiration into the lungs can cause CNS (central nervous system) and subsequent aspiration into the lungs can cause pulmonary edema and chemical pneumonia depression. Chronic overexposure in high concentrations may produce CNS depression.

Ingestion:Irritation of the mouth, esophagus, and stomach can develop following ingestion. Symptoms include burning of the mouth, sore throat, vomiting, nausea, dizziness, loss of consciousness. Due to its light viscosity, there is danger of aspiration into the lungs during vomiting. Aspiration can result in severe lung damage or death.

Skin Contact:Prolonged or repeated skin contact may cause moderate to severe irritation including itching and redness of the skin, defatting, and/or dermatitis. This product can also be absorbed through the skin and produce CNS symptoms. Single prolonged exposure is not likely to result in the product being absorbed through the skin in harmful amounts.

Signs And Symptoms Of Exposure: Eye irritation, respiratory irritation, drying and cracking of skin, dizziness, fatigue, headache, unconsciousness or asphyxiation. Chronic effects of ingestion and subsequent aspiration into the lungs can cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Repeated breathing of vapours can cause effects to liver and kidneys. Treat symptomatically.

Eyes Causes serious eye irritation.

Skin May cause an allergic skin reaction. Causes skin irritation.



SDS Revision Date: 02/02/2024

Section 12. Ecological information

Toxicity

Toxic to aquatic life with long lasting effects.

Toxic to aquatic life

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,
	mg/L	mg/L	mg/L
1-Propoxy-2-propanol - (1569-01-3)	{CalcFish}	{CalcCrust}	{CalcAlgae}

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

No available information

Mobility in soil

No available information

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No available information

Section 13. Disposal considerations

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.



.

SDS Revision Date: 02/02/2024

Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

Classification Method: Classified as per Part 2, Sections 2.1 - 2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface	IMO / IMDG (Ocean	ICAO/IATA
	Transportation)	Transportation)	
UN number	UN3175	UN3175	UN3175
UN proper	Solids containing	Solids containing	Solids containing
shipping	flammable liquid, n.o.s. (1-	flammable liquid, n.o.s. (1-	flammable liquid, n.o.s. (1-
name	propoxy-2-propanol),4.1,II	propoxy-2-propanol),4.1,II	propoxy-2-propanol),4.1,II
Transport	TDG Hazard Class:4.1	IMDG:4.1	Air Class:4.1
hazard	Sub Class:Not Applicable	Sub Class:Not Applicable	Sub Class:Not Applicable
class(es)			
Packing	II	II	II
group			

Environmental hazards

Marine Pollutant: Yes;

Special precautions for user

No available information

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

1-Propoxy-2-propanol

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.



SDS Revision Date: 02/02/2024

Section 16. Other information	

<u>NFPA</u>	Health Hazards Not determined	Flammability Not determined	Instability Not determined	Special Hazards Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards 0	Personal Protection

SDS Revision Date 10/25/2023

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

End of Document