



### Section 1. Identification

**Product identifier** 469BULK

**Product Identity** Slide Bulk Mold Cleaner 4

**Other means of identification** Slide Bulk Mold Cleaner 4  
( SDS applies to pint, 1G, 5G, and 55G sizes )

#### Relevant identified uses of the substance or mixture and uses advised against

Industrial Mold Cleaner

#### Details of the supplier of the safety data sheet

**Company Name** Slide Products Inc.  
430 Wheeling Road  
Wheeling, IL 60090

**Initial Supplier Identifier:** THIS SAFETY DATA SHEET IS NOT COMPLIANT UNLESS  
CANADIAN ADDRESS IS USED  
PLEASE CONTACT A CANADIAN SLIDE DISTRIBUTOR FOR THE  
FULLY COMPLIANT SDS FILE

**Emergency**

**24 hour Emergency Telephone No.** Emergency Telephone INFOTRAC 1-352-323-3500  
(International)  
1-800-535-5053 (North America)

**Customer Service:** Phone: 1-847-541-7220  
Fax: 1-847-541-7986

### Section 2. Hazard(s) identification

#### Classification of the substance or mixture

Extremely flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye irritation.  
Very toxic to aquatic life with long lasting effects.

**Label elements****Danger**

Extremely flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause drowsiness and dizziness.  
Very toxic to aquatic life with long lasting effects.

**[Prevention]:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.  
Keep container tightly closed.  
Keep cool.  
Ground and bond container and receiving equipment.  
Use explosion-proof electrical, ventilating, light, equipment.  
Use non-sparking tools.  
Take action to prevent static discharges.  
Avoid breathing dust, fume, gas, mist, vapours, spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Avoid release to the environment.  
Wear protective gloves, eye protection, and face protection.

**[Response]:**

IF ON SKIN: Wash with plenty of soap and water.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Call a POISON CENTER, doctor or physician if you feel unwell.  
If skin irritation occurs: Get medical attention.  
If eye irritation persists: Get medical advice or attention.  
Take off contaminated clothing and wash it before reuse.  
In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.  
Collect spillage.



**[Storage]:**

Store in a well ventilated place. Keep container tightly closed.  
Store in a well ventilated place. Keep cool.  
Store locked up.

**[Disposal]:**

Dispose of contents or container in accordance with local and national regulations.

**Section 3. Composition/information on ingredients**

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Isopropyl Alcohol CAS Number: 67-63-0 Synonyms: ISOPROPANOL, Propan-2-ol, ISOPROPYL ALCOHOL (manufacture-strong acid process, Solvent C-3)	40 - 60	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	----
Heptane CAS Number: 142-82-5 Synonyms: n-Heptane	40 - 60	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Skin Irrit. 2;H315 STOT SE 3;H336 Aquatic Chronic 1;H410	----

The actual concentration or concentration range is withheld as a trade secret.

\*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

**Section 4. First aid measures****Description of first aid measures**

- General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

**Most important symptoms and effects, both acute and delayed**

**Overview** No chronic toxicity or long term toxicity information available. Treat symptomatically. Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

- Eyes** Causes serious eye irritation.
- Skin** Causes skin irritation.

**Section 5. Fire-fighting measures****Extinguishing media**

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Unsuitable extinguishing media: Do not use; water jet.

**Special hazards arising from the substance or mixture**

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.  
Keep container tightly closed.  
Keep cool.  
Ground and bond container and receiving equipment.  
Use explosion-proof electrical, ventilating, light, equipment.  
Use non-sparking tools.  
Take action to prevent static discharges.  
Avoid breathing dust, fume, gas, mist, vapours, spray.

**Advice for fire-fighters**

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

**Section 6. Accidental release measures****Personal precautions, protective equipment and emergency procedures**

Put on appropriate personal protective equipment (see section 8).  
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

**Environmental precautions**

Do not allow spills to enter drains or waterways.

**Methods and material for containment and cleaning up**

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

**Section 7. Handling and storage****Precautions for safe handling**

Handle containers carefully to prevent damage and spillage.  
See section 2 for further details. - [Prevention]:

**Conditions for safe storage, including any incompatibilities**

Incompatible materials: Strong oxidizing agents and acids.  
See section 2 for further details. - [Storage]:

**Specific end use(s)**

No available information

**Section 8. Exposure controls / personal protection**

**Control parameters**

**Exposure Limits**

CAS No.	Ingredient	Source	Value
67-63-0	Isopropyl Alcohol	ACGIH	TWA: 200 ppm STEL: 400 ppm
		Alberta	200 ppm TWA; 492 mg/m <sup>3</sup> TWA 400 ppm STEL; 984 mg/m <sup>3</sup> STEL
		British Columbia	200 ppm TWA 400 ppm STEL
		Manitoba	200 ppm TWA 400 ppm STEL
		New Brunswick	400 ppm TWA; 983 mg/m <sup>3</sup> TWA 500 ppm STEL; 1230 mg/m <sup>3</sup> STEL
		Newfoundland and Labrador	200 ppm TWA 400 ppm STEL
		Nova Scotia	200 ppm TWA 400 ppm STEL
		Northwest Territories	200 ppm TWA 400 ppm STEL
		Nunavut	200 ppm TWA 400 ppm STEL
		Ontario	200 ppm TWA 400 ppm STEL
		Prince Edward Island	200 ppm TWA 400 ppm STEL
		Quebec	400 ppm TWAEV; 985 mg/m <sup>3</sup> TWAEV 500 ppm STEV; 1230 mg/m <sup>3</sup> STEV
		Saskatchewan	200 ppm TWA 400 ppm STEL
Yukon	400 ppm TWA; 980 mg/m <sup>3</sup> TWA 500 ppm STEL; 1225 mg/m <sup>3</sup> STEL		
142-82-5	Heptane	ACGIH	TWA: 200 ppm STEL: 400 ppm
		Alberta	400 ppm TWA; 1640 mg/m <sup>3</sup> TWA 500 ppm STEL; 2050 mg/m <sup>3</sup> STEL
		British Columbia	400 ppm TWA 500 ppm STEL
		Manitoba	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		New Brunswick	400 ppm TWA; 1640 mg/m <sup>3</sup> TWA 500 ppm STEL; 2050 mg/m <sup>3</sup> STEL
		Newfoundland and Labrador	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		Nova Scotia	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		Northwest Territories	400 ppm TWA 500 ppm STEL
		Nunavut	400 ppm TWA 500 ppm STEL
		Ontario	400 ppm TWA 500 ppm STEL (listed under Heptane, all isomers)
		Prince Edward Island	400 ppm TWA (listed under Heptane, all isomers) 500 ppm STEL (listed under Heptane, all isomers)
		Quebec	400 ppm TWAEV; 1640 mg/m <sup>3</sup> TWAEV 500 ppm STEV; 2050 mg/m <sup>3</sup> STEV
		Saskatchewan	400 ppm TWA 500 ppm STEL
Yukon	400 ppm TWA; 1600 mg/m <sup>3</sup> TWA 500 ppm STEL; 2000 mg/m <sup>3</sup> STEL		

**Exposure controls**

**Respiratory**

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

**Eyes**

Protective safety glasses recommended

**Skin**

Avoid skin contact. Protective gloves recommended.

**Engineering Controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

**Other Work Practices**

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

**Section 9. Physical and chemical properties**

<b>Appearance</b>	Clear Liquid
<b>Odor</b>	Not Available
<b>Odor threshold</b>	No available information
<b>pH</b>	Not determined
<b>Melting point / freezing point</b>	Not determined
<b>Initial boiling point and boiling range</b>	70.6 °C / 159 °F
<b>Flash Point</b>	<-3.9 °C / <25 °F
<b>Evaporation rate (Ether = 1)</b>	Faster than ether Minutes
<b>Flammability (solid, gas)</b>	Flammable Liquid
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> 1.2% <b>Upper Explosive Limit:</b> 7.5%
<b>Vapour pressure (Pa)</b>	0.735 @ 21°C (70°F)
<b>Vapour Density</b>	Heavier than air (Air=1)
<b>Relative Density</b>	0.675 (Water=1)
<b>Solubility in Water</b>	No available information
<b>Partition coefficient n-octanol/water (Log Kow)</b>	No available information
<b>Auto-ignition temperature</b>	Not determined
<b>Decomposition temperature</b>	Not determined
<b>Viscosity (cSt)</b>	Not determined
<b>VOC Content</b>	100 %
<b>Oxidising properties</b>	Not determined
<b>Explosive properties</b>	Not determined
<b>Other information</b>	
No other relevant information.	

**Section 10. Stability and reactivity****Reactivity**

Hazardous Polymerization will not occur.

**Chemical stability**

Stable under normal circumstances.

**Possibility of hazardous reactions**

No available information

**Conditions to avoid**

Excessive heat and open flame.

**Incompatible materials**

Strong oxidizing agents and acids.

**Hazardous decomposition products**

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

**Section 11. Toxicological information****Acute toxicity**

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).



**Safety Data Sheet**  
**Slide Bulk Mold Cleaner 4**

**SDS Revision Date:**  
**16 June, 2026**

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Isopropyl Alcohol - (67-63-0)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Heptane - (142-82-5)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}

### Carcinogen Data

CAS No.	Ingredient	Source	Value
67-63-0	Isopropyl Alcohol	IARC	Group 3
		ACGIH	A4
142-82-5	Heptane	IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-single exposure (3)	3	May cause drowsiness or dizziness.
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

### Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

### Symptoms and effects, both acute and delayed:

No chronic toxicity or long term toxicity information available. Treat symptomatically.

<b>Inhalation</b>	May cause drowsiness or dizziness.
<b>Eyes</b>	Causes serious eye irritation.
<b>Skin</b>	Causes skin irritation.

**Section 12. Ecological information**

**Toxicity**

Very toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

**Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Isopropyl Alcohol - (67-63-0)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Heptane - (142-82-5)	{CalcFish}	{CalcCrust}	{CalcAlgae}

**Persistence and degradability**

There is no data available on the preparation itself.

**Bioaccumulative potential**

No available information

**Mobility in soil**

No available information

**Results of PBT and vPvB assessment**

This product contains no PBT/vPvB/vPvM chemicals.

**Other adverse effects**

No available information

**Section 13. Disposal considerations**

**Waste treatment methods**

Observe all federal, provincial and local regulations when disposing of this substance.

**Section 14. Transport information**

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

	<b>TDG (Domestic Surface Transportation)</b>	<b>IMO / IMDG (Ocean Transportation)</b>	<b>ICAO/IATA</b>
<b>UN number</b>	UN1993	UN1993	UN1993
<b>UN proper shipping name</b>	Flammable liquid, n.o.s., (Heptane, Isopropanol)	Flammable liquid, n.o.s., (Heptane, Isopropanol)	Flammable liquid, n.o.s., (Heptane, Isopropanol)
<b>Transport hazard class(es)</b>	<b>Class:</b> 3 <b>Sub Class:</b> Not Applicable	<b>Class:</b> 3 <b>Sub Class:</b> Not Applicable	<b>Class:</b> 3 <b>Sub Class:</b> Not Applicable
<b>Packing group</b>	II	II	II

**Environmental hazards**

IMDG Marine Pollutant: Yes; ( Heptane )

**Special precautions for user**

No available information

**Section 15. Regulatory information**

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) and the SDS contains all of the information required by those regulations.

**Canadian Domestic Substance List (DSL):**

- Heptane
- Isopropyl Alcohol

**Canadian Non-Domestic Substance List (NDSL):**

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

**Section 16. Other information**

**SDS Revision Date** 16 June, 2026

<b><u>NFPA</u></b>	<b>Health Hazards</b> Not determined	<b>Flammability</b> Not determined	<b>Instability</b> Not determined	<b>Special Hazards</b> Not determined
<b><u>HMIS</u></b>	<b>Health Hazards</b> 2	<b>Flammability</b> 3	<b>Physical Hazards</b> 0	<b>Personal Protection</b> X

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness and dizziness.
- H410 Very toxic to aquatic life with long lasting effects.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

**End of Document**