

Section 1. Identification				
1.1. Product identifier	60883-35			
Product Identity Alternate Names	Slide 5 % Wax Casting Mold Release Slide 5 % Wax Casting Mold Release			
1.2. Relevant identified uses of the substance or mixture and uses advised against				
Intended use	Industrial Mold Release			
1.3. Details of the supplier of the safety data sheet				
Company Name	Slide Products Inc. 430 Wheeling Road Wheeling, IL 60090			
Emergency 24 hour Emergency Telephone No.	Emergency Telephone INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)			
Customer Service:	Phone: 1-847-541-7220 Fax: 1-847-541-7986			

Section 2. Hazard(s) identification

2.1. Classification of the substance or mixture

Extremely flammable gas. Contains gas under pressure; may explode if heated. May cause drowsiness or dizziness. May displace oxygen and cause rapid suffocation.



2.2. Label elements



Danger

Extremely flammable gas. Contains gas under pressure; may explode if heated. May cause drowsiness and dizziness. May displace oxygen and cause rapid suffocation.

[Prevention]:

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Keep container tightly closed. Avoid breathing dust, fume, gas, mist, vapors, spray. Use only outdoors or in a well-ventilated area. [Response]:

IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
Call a POISON CENTER, doctor or physician if you feel unwell.
Leaking gas fire - do not extinguish unless leak can be stopped safely.
In case of leakage, eliminate all ignition sources.
[Storage]:

Store in a well ventilated place. Keep container tightly closed.Store in a well ventilated place. Keep cool.Store locked up.Protect from sunlight. Store in a well ventilated place.[Disposal]:

Dispose of contents or container in accordance with local and national regulations.



Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Dimethyl ether CAS Number: 115-10-6	50 - 75	Flam. Gas 1;H220	
1,1-Difluoroethane CAS Number: 75-37-6	25 - 50	Flam. Gas 1;H220 Liquified Gas;H280 STOT SE 3;H336 Simple Asphyxiant	
Oxirane CAS Number: 9038-95-3	1 - 7	Not Classified	

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

- **General** In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- **Inhalation** Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
- **Eyes** Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
- **Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
- **Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.



4.2. Most important symptoms and effects, both acute and delayed

Overview Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. Check section 2.2 (GHS Label Elements) for further details.

Inhalation May cause drowsiness or dizziness.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray. Unsuitable extinguishing media: Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat, sparks, open flames, and other ignition sources - No smoking. Keep container tightly closed.

Avoid breathing dust, fume, gas, mist, vapors, spray.

5.3. Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No.



Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8). Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage. Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong oxidizing agents and acids. Check section 2.2 (GHS Label Elements) for further details. - [Storage]:

7.3. Specific end use(s)

No available information



Section 8. Exposure controls / personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value	
75-37-6	1,1-Difluoroethane	OSHA	No Established Limit	
ACGIH	No Established Limit			
NIOSH	No Established Limit			
115-10-6	Dimethyl ether	OSHA	No Established Limit	
ACGIH	TWA: 1000 ppm			
NIOSH	No Established Limit			
9038-95-3	Oxirane	OSHA	No Established Limit	
ACGIH	No Established Limit			
NIOSH	No Established Limit			

8.2. Exposure

controls	
Respiratory	If workers are exposed to concentrations above the exposure limit they must use
	the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Avoid skin contact. Protective gloves recommended.
Engineering	Provide adequate ventilation. Where reasonably practicable this should be
Controls	achieved by the use of local exhaust ventilation and good general extraction. If
	these are not sufficient to maintain concentrations of particulates and any vapor
	below occupational exposure limits suitable respiratory protection must be worn.
Other Work	Use good personal hygiene practices. Wash hands before eating, drinking,
Practices	smoking or using toilet. Promptly remove soiled clothing and wash thoroughly
	before reuse.

Check section 2.2 (GHS Label Elements) for further details. - [Prevention]:



Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Pressurized aerosol dispensed as a mist.
Color	Clear, Colorless
Odor	Slight Ethereal Odor
Odor threshold	No available information
рН	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	No available information
Flash Point	°F °C, Test method: (Open/Close cup)
Evaporation rate (Ether = 1)	No available information
Flammability (solid, gas)	Gas
Upper/lower flammability or explosive limits	Lower Explosive Limit: No available
	information
	Upper Explosive Limit: No available
	information
Vapor pressure (Pa)	64.0 psig
Vapor Density	2
Relative Density	0.83
Solubility in Water	No available information
Partition coefficient n-octanol/water (Log	No available information
Kow)	
Auto-ignition temperature	No available information
Decomposition temperature	No available information
Viscosity (cSt)	No available information
Oxidising properties	No available information
Evelopius preventies	
Explosive properties	No available information
Water Solubility	No available information Slightly soluble

9.2. Other information No other relevant information.



Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No available information

10.4. Conditions to avoid

Excessive heat and open flame.

10.5. Incompatible materials

Strong oxidizing agents and acids.

10.6. Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Dimethyl ether - (115-10-6)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
1,1-Difluoroethane - (75-37-6)					



Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}
Oxirane - (9038-95-3)	{calcoral}	{CalcDerm}	{CalcInhV}	{CalcInhDM}	{CalcInhG}

Carcinogen Data

CAS No.	Ingredient	Source	Value
75-37-6	1,1-Difluoroethane	OSHA	Regulated Carcinogen: No
NTP	Known: No; Suspected: No		
IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
ACGIH	No Established Limit		
115-10-6	Dimethyl ether	OSHA	Regulated Carcinogen: No
NTP	Known: No; Suspected: No		
IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
ACGIH	No Established Limit		
9038-95-3	Oxirane	OSHA	Regulated Carcinogen: No
NTP	Known: No; Suspected: No		
IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;		
ACGIH	No Established Limit		

Classification	Category	Hazard Description
Acute toxicity (oral)		Not Applicable
Acute toxicity (dermal)		Not Applicable
Acute toxicity (inhalation)		Not Applicable
Skin corrosion/irritation		Not Applicable
Serious eye damage/irritation		Not Applicable
Respiratory sensitization		Not Applicable
Skin sensitization		Not Applicable
Germ cell mutagenicity		Not Applicable
Carcinogenicity		Not Applicable
Reproductive toxicity		Not Applicable
STOT-single exposure	3	May cause drowsiness or dizziness.
STOT-single exposure		Not Applicable
STOT-repeated exposure		Not Applicable
Aspiration hazard		Not Applicable



Section 12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data. **Aquatic Ecotoxicity**

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Dimethyl ether - (115-10-6)	{CalcFish}	{CalcCrust}	{CalcAlgae}
1,1-Difluoroethane - (75-37-6)	{CalcFish}	{CalcCrust}	{CalcAlgae}
Oxirane - (9038-95-3)	{CalcFish}	{CalcCrust}	{CalcAlgae}

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

No available information

12.4. Mobility in soil

No available information

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No available information

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.



Section 14. Transport information

When shipped in containers of 0.3 gallons (1 L) or less this material may be reclassified in accordance with DOT regulations 49 CFR 173.150 / IATA DGR packing instruction Y341/ IMDG Code 3.4 as: Limited Quantity.

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN	UN1954	UN1954	UN1954
number			
14.2. UN	Compressed gas,	Compressed gas,	Compressed gas,
proper	flammable, n.o.s., (flammable, n.o.s., (flammable, n.o.s., (
shipping	Dimethyl ether, 1,1-	Dimethyl ether, 1,1-	Dimethyl ether, 1,1-
name	Difluorothane)	Difluorothane)	Difluorothane)
14.3.	DOT Hazard Class:2.1	IMDG:2.1	Air Class:2.1
Transport	Sub Class:Not Applicable	Sub Class:Not Applicable	Sub Class:Not Applicable
hazard class(es)			
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable

14.5. Environmental hazards

Marine Pollutant: No; 14.6. Special precautions for user

No available information



Act (TSCA)

Section 15. Regulatory information				
Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.			
Toxic Substance Control	All components of this material are either listed or exempt from			

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

listing on the TSCA Inventory.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



Section 16. Other information				
<u>NFPA</u>	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined
<u>HMIS</u>	Health Hazards	Flammability	Physical Hazards	Personal Protection
	1	3	0	B

SDS Revision Date

02/01/2024

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H336 May cause drowsiness and dizziness.

End of Document