

TECHNICAL DATA SHEET



Econo-Spray 3 Release Bulk/Liquid 40801PB, 40805PB, 40855PB

Product Description

Econo-Spray® 3 contains a highly effective non-silicone release in a non-chlorinated solvent carrier system. This product is highly paintable, and will permit ultra-sonic welding of molded parts. It affords excellent release of all thermoplastics.

Applications

Mold Release

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Paintable Mold Release

Approx. Net Weight Fill per Gal.

6 pounds

Net Weight Fill

1 - 55 gallons

Appearance

Clear Oily Colorless Liquid

Odor

Mild, Petroleum-like

Flash Point F

25 degrees

Flash Point C

Negative 4 degrees

Base Type

Propylene Glycol

Evaporation Rate

Fast

HMIS Rating

2, 3, 0, X

DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

VOC % (Federal)

96.67

VOC g/L (Federal)

683.05

VOC lbs./Gal (Federal)

5.7

Removal

Remove with organic or hydrocarbon solvents

Food Safety Citation (CFR)

21CFR 178.3570

Units Per Case

1

Case Weight (lbs)

Various

Working Temperature F

32 to 600 degrees

Working Temperature C

0 to 315 degrees

Specific Gravity

0.698