

TECHNICAL DATA SHEET

Zinc Stearate Mold Release Aerosol

41012N

Product Description

A dry, light, water-repellent powder, Zinc Stearate is economical to use and gives better finishes. Use it for polycarbonates, polypropylenes, polysulfones and rubber molding. Compatible with oil-based paints, its formulation results in fewer rejects and lower production costs.

Applications

Mold Release

Shelf Life

Three years from Date of Manufacture (as found on the bottom of each can and shipping box)

Unit Package Description

16 ounce aerosol

Generic Description

Mold Release

Net Weight Fill

11.5 net ounces

UPC Code

858799000103

Appearance

White Powder

Odor

Mild, Petroleum like

Flash Point F

Not Applicable

Flash Point C

Not Applicable

Base Type

Zinc Stearate

Evaporation Rate

Fast

HMIS Rating

1, 3, 0, B

DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

VOC % (Federal)

59.17

VOC g/L (Federal)

446.93

VOC lbs./Gal (Federal)

3.72

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

12

Case Weight (lbs)

13

Working Temperature F

32 to 600 degrees

Working Temperature C

0 to 315 degrees

Propellant

DME/152A

NFPA Aerosol Flammability Level

1

