

TECHNICAL DATA SHEET



DFL Dry Film Lube Mold Release Aerosol 41112N

Product Description

DFL is an excellent, fast-drying release agent for injection molding where clarity and deep draw are important, especially with hard, brittle resins. It will not create "hydraulic effect" on deep drafted molds. Its "dry" formulation will not pick up dust or dirt and remains inert when exposed to corrosive reagents.

Applications

Mold Release

Unit Package Description

16 ounce aerosol

Generic Description

Dry Film Mold Release

Net Weight Fill

11.5 net ounces

UPC Code

858799000943

Appearance

Slight White Coating

Odor

Alcohol

Flash Point F

Not Applicable

Flash Point C

Not Applicable

Base Type

PTFE

Evaporation Rate

Fast

HMIS Rating

1, 3, 0, B

DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

VOC % (Federal)

51.73

VOC g/L (Federal)

399.31

VOC lbs./Gal (Federal)

3.33

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

12

Case Weight (lbs)

13

Working Temperature F

32 to 450 degrees

Working Temperature C

0 to 232 degrees

Propellant

DME/152A

NFPA Aerosol Flammability Level

1