

TECHNICAL DATA SHEET



DuraKote Release Bulk/Liquid 41701PB, 41705PB, 41755PB

Product Description	Dura Kote is a special air-drying release that will not transfer onto the molded part. It provides a dry, dust-free film on all hard-surfaced molds. It won't discolor and is paintable when it is baked on.
Applications	Mold Release
Unit Package Description	1, 5 and 55-gallon containers
Generic Description	Semi-Permanent Mold Release
Approx. Net Weight Fill per Gal.	8 pounds
Net Weight Fill	1 - 55 gallons
Appearance	Clear Oily Colorless Liquid
Odor	Mild, Petroleum-like
Flash Point F	25 degrees
Flash Point C	Negative 4 degrees
Base Type	Curable Silicone Fluid
Evaporation Rate	Fast
HMIS Rating	2, 3, 0, X
DOT Proper Shipping Name	UN1993, Proper Shipping Name - Flammable Liquid, n.o.s. (Heptane, Isopropanol), Hazard Class - 3, Packing Group - II
VOC % (Federal)	99
VOC g/L (Federal)	949.03
VOC lbs./Gal (Federal)	7.92
Removal	Remove with organic or hydrocarbon solvents
Units Per Case	1
Case Weight (lbs)	Various
Working Temperature F	32 to 600 degrees
Working Temperature C	0 to 315 degrees
Specific Gravity	0.675