

## TECHNICAL DATA SHEET



### DuraKote Release Bulk/Liquid 41701PB, 41705PB, 41755PB

<b>Product Description</b>	Dura Kote is a special air-drying release that will not transfer onto the molded part. It provides a dry, dust-free film on all hard-surfaced molds. It won't discolor and is paintable when it is baked on.
<b>Applications</b>	Mold Release
<b>Unit Package Description</b>	1, 5 and 55-gallon containers
<b>Generic Description</b>	Semi-Permanent Mold Release
<b>Approx. Net Weight Fill per Gal.</b>	8 pounds
<b>Net Weight Fill</b>	1 - 55 gallons
<b>Appearance</b>	Clear Oily Colorless Liquid
<b>Odor</b>	Mild, Petroleum-like
<b>Flash Point F</b>	25 degrees
<b>Flash Point C</b>	Negative 4 degrees
<b>Base Type</b>	Curable Silicone Fluid
<b>Evaporation Rate</b>	Fast
<b>HMIS Rating</b>	2, 3, 0, X
<b>DOT Proper Shipping Name</b>	UN1993, Proper Shipping Name - Flammable Liquid, n.o.s. (Heptane, Isopropanol), Hazard Class - 3, Packing Group - II
<b>VOC % (Federal)</b>	99
<b>VOC g/L (Federal)</b>	949.03
<b>VOC lbs./Gal (Federal)</b>	7.92
<b>Removal</b>	Remove with organic or hydrocarbon solvents
<b>Units Per Case</b>	1
<b>Case Weight (lbs)</b>	Various
<b>Working Temperature F</b>	32 to 600 degrees
<b>Working Temperature C</b>	0 to 315 degrees
<b>Specific Gravity</b>	0.675