

TECHNICAL DATA SHEET



SSL Mold Release Bulk/Liquid 42101PB, 42105PB, 42155PB

Product Description	SSL Mold Release is an economical Silicone-based mold release. NSF-certified formulation that is safe for food applications. Non-paintable.
Applications	Mold Release
Unit Package Description	1, 5 and 55-gallon containers
Generic Description	Silicone Mold Release
Approx. Net Weight Fill per Gal.	6 pounds
Net Weight Fill	1 - 55 gallons
Appearance	Clear Oily Colorless Liquid
Odor	Mild, Petroleum-like
Flash Point F	25 degrees
Flash Point C	Negative 4 degrees
Base Type	Silicone
Evaporation Rate	Fast
HMIS Rating	2, 3, 0, X
DOT Proper Shipping Name	UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II
VOC % (Federal)	95
VOC g/L (Federal)	675.58
VOC lbs./Gal (Federal)	5.64
Removal	Remove with organic or hydrocarbon solvents
Food Safety Citation (CFR)	21CFR 175.300
Units Per Case	1
Case Weight (lbs)	Various
Working Temperature F	32 to 600 degrees
Working Temperature C	0 to 315 degrees
Specific Gravity	0.698