

TECHNICAL DATA SHEET



SSL Mold Release Bulk/Liquid 42101PB, 42105PB, 42155PB

| | |
|---|---|
| Product Description | SSL Mold Release is an economical Silicone-based mold release. NSF-certified formulation that is safe for food applications. Non-paintable. |
| Applications | Mold Release |
| Unit Package Description | 1, 5 and 55-gallon containers |
| Generic Description | Silicone Mold Release |
| Approx. Net Weight Fill per Gal. | 6 pounds |
| Net Weight Fill | 1 - 55 gallons |
| Appearance | Clear Oily Colorless Liquid |
| Odor | Mild, Petroleum-like |
| Flash Point F | 25 degrees |
| Flash Point C | Negative 4 degrees |
| Base Type | Silicone |
| Evaporation Rate | Fast |
| HMIS Rating | 2, 3, 0, X |
| DOT Proper Shipping Name | UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II |
| VOC % (Federal) | 95 |
| VOC g/L (Federal) | 675.58 |
| VOC lbs./Gal (Federal) | 5.64 |
| Removal | Remove with organic or hydrocarbon solvents |
| Food Safety Citation (CFR) | 21CFR 175.300 |
| Units Per Case | 1 |
| Case Weight (lbs) | Various |
| Working Temperature F | 32 to 600 degrees |
| Working Temperature C | 0 to 315 degrees |
| Specific Gravity | 0.698 |