

## TECHNICAL DATA SHEET



### Universal Release Bulk/Liquid 42601HB, 42605HB, 42655HB

#### Product Description

Universal is just that, a broad universal release that can be used on all thermoplastics, even more sensitive plastics. It uses a non-silicone and paintable release oil. Universal Mold Release also meets certain requirements for molding medical products - contact us for details. Universal will not interfere with part bonding, heat sealing, laminating, ultrasonic welding or post-decorating.

#### Applications

Mold Release

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Paintable Mold Release

#### Approx. Net Weight Fill per Gal.

6 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Clear Oily Colorless Liquid

#### Odor

Mild, Petroleum-like

#### Flash Point F

25 degrees

#### Flash Point C

Negative 4 degrees

#### Base Type

White Oil

#### Evaporation Rate

Fast

#### HMIS Rating

2, 3, 0, G

#### DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

95

#### VOC g/L (Federal)

749.71

#### VOC lbs./Gal (Federal)

6.25

#### Removal

Remove with organic or hydrocarbon solvents

#### Food Safety Citation (CFR)

21CFR 172.878 and 178.3620 (a)

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 600 degrees

#### Working Temperature C

0 to 315 degrees

#### Specific Gravity

0.791