

TECHNICAL DATA SHEET



Quick Rust Preventive Bulk/Liquid 42801RPB, 42805RPB, 42855RPB

Product Description

Slide Quick RP employs a combination of fast evaporating solvents and oils to set up quickly on your mold surfaces, providing immediate protection against moisture and light acids. This unique "dry" package makes clean-up quick and easy when the mold is put back into production, saving time and money. The red tracing dye allows for visual verification of complete mold coverage.

Applications

Rust Preventive

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Rust Preventive

Approx. Net Weight Fill per Gal.

6 pounds

Net Weight Fill

1 - 55 gallons

Appearance

Red-Tint Liquid

Odor

Mild, Petroleum like

Flash Point F

25 degrees

Flash Point C

Negative 4 degrees

Base Type

Lecithin

Evaporation Rate

Moderate

HMIS Rating

2, 3, 0, X

DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

VOC % (Federal)

87

VOC g/L (Federal)

625.49

VOC lbs./Gal (Federal)

5.22

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

1

Case Weight (lbs)

Various

Working Temperature F

32 to 350 degrees

Working Temperature C

0 to 176 degrees

Specific Gravity

0.698