

## TECHNICAL DATA SHEET



### Quick Rust Preventive Bulk/Liquid 42801RPB, 42805RPB, 42855RPB

#### Product Description

Slide Quick RP employs a combination of fast evaporating solvents and oils to set up quickly on your mold surfaces, providing immediate protection against moisture and light acids. This unique "dry" package makes clean-up quick and easy when the mold is put back into production, saving time and money. The red tracing dye allows for visual verification of complete mold coverage.

#### Applications

Rust Preventive

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Rust Preventive

#### Approx. Net Weight Fill per Gal.

6 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Red-Tint Liquid

#### Odor

Mild, Petroleum like

#### Flash Point F

25 degrees

#### Flash Point C

Negative 4 degrees

#### Base Type

Lecithin

#### Evaporation Rate

Moderate

#### HMIS Rating

2, 3, 0, X

#### DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

87

#### VOC g/L (Federal)

625.49

#### VOC lbs./Gal (Federal)

5.22

#### Removal

Remove with organic or hydrocarbon solvents

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 350 degrees

#### Working Temperature C

0 to 176 degrees

#### Specific Gravity

0.698