

## TECHNICAL DATA SHEET



### Urethane Release Bulk/Liquid 45801PB, 45805PB, 45855PB

#### Product Description

Urethane Mold Release is extremely effective for all polyurethanes: rigid, semi-rigid and flexible urethane foams. Urethane mold release imparts a light, dry coating on the mold, eliminating build-up. Yet, it is so effective that it continues to work for several cycles between applications. Non-paintable formulation.

#### Applications

Mold Release

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Mold Release for Urethane Resins

#### Approx. Net Weight Fill per Gal.

7 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Clear Oily Colorless Liquid

#### Odor

Mild, Petroleum-like

#### Flash Point F

25 degrees

#### Flash Point C

Negative 4 degrees

#### Base Type

Silicone

#### Evaporation Rate

Fast

#### HMIS Rating

2, 3, 0, X

#### DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

93

#### VOC g/L (Federal)

666.42

#### VOC lbs./Gal (Federal)

5.56

#### Removal

Remove with organic or hydrocarbon solvents

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 500 degrees

#### Working Temperature C

0 to 260 degrees

#### Specific Gravity

0.698