

TECHNICAL DATA SHEET



Urethane Mold Release Aerosol

45812H

Product Description

Urethane mold release is extremely effective for all polyurethanes: rigid, semi-rigid and flexible urethane foams. Urethane mold release imparts a light, dry coating on the mold, eliminating build-up. Yet, it is so effective that it continues to work for several cycles between applications. Non-paintable formulation.

Applications

Mold Release

Shelf Life

Three years from Date of Manufacture (as found on the bottom of each can and shipping box)

Unit Package Description

16 ounce aerosol

Generic Description

Mold Release for Urethane Resins

Net Weight Fill

11.5 net ounces

UPC Code

858799000585

Appearance

Clear Oily Colorless Liquid

Odor

Ether like

Flash Point F

Not Applicable

Flash Point C

Not Applicable

Base Type

Silicone

Evaporation Rate

Fast

HMIS Rating

1, 3, 0, B

DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

VOC % (Federal)

57.78

VOC g/L (Federal)

431.97

VOC lbs./Gal (Federal)

3.6

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

12

Case Weight (lbs)

13

Working Temperature F

32 to 500 degrees

Working Temperature C

0 to 260 degrees

Propellant

DME/152A

NFPA Aerosol Flammability Level

1