


## TECHNICAL DATA SHEET



### Knock Out Mold Release Bulk/Liquid 46601PB, 46605PB, 46655PB

#### Product Description

Knock Out is the mold release that works where others have failed. It gets "sticky parts" cleanly out of the mold and is approved for indirect food contact. Knock Out Mold Release imparts a light, dry coating that is amazingly effective, working for several cycles without re-application. Paintable formulation.

#### Applications

Mold Release

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Paintable Mold Release

#### Approx. Net Weight Fill per Gal.

6 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Clear Oily Colorless Liquid

#### Odor

Mild, Petroleum-like

#### Flash Point F

25 degrees

#### Flash Point C

Negative 4 degrees

#### Base Type

Propylene Glycol

#### Evaporation Rate

Fast

#### HMIS Rating

2, 3, 0, X

#### DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

96.67

#### VOC g/L (Federal)

683.99

#### VOC lbs./Gal (Federal)

5.71

#### Removal

Remove with organic or hydrocarbon solvents

#### Food Safety Citation (CFR)

21CFR 178.3570

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 450 degrees

#### Working Temperature C

0 to 232 degrees

#### Specific Gravity

0.698

