


## TECHNICAL DATA SHEET



### White Rhino Rust Preventive Bulk/Liquid 46701PB, 46705PB, 46755PB

#### Product Description

White Rhino Rust Preventive wraps your mold in a tough, protective second skin. It's ideal for plastics processing for food applications. Fast-drying formulation sets up quickly to protect immediately against moisture and light acids. Self-cleaning in startup. White Rhino is NSF-certified as safe for use on food machinery and molds.

#### Applications

Rust Preventive

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Rust Preventive

#### Approx. Net Weight Fill per Gal.

6 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Brownish-Tint Liquid

#### Odor

Mild, Petroleum like

#### Flash Point F

25 degrees

#### Flash Point C

Negative 4 degrees

#### Base Type

Petroleum

#### Evaporation Rate

Slow

#### HMIS Rating

2, 3, 0, X

#### DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

81

#### VOC g/L (Federal)

887.91

#### VOC lbs./Gal (Federal)

7.41

#### Removal

Remove with organic or hydrocarbon solvents

#### Food Safety Citation (CFR)

NSF H1

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 350 degrees

#### Working Temperature C

0 to 176 degrees

#### Specific Gravity

0.698

