## SLIDE.

## **TECHNICAL DATA SHEET**









## White Rhino Rust Preventive Bulk/Liquid 46701PB, 46705PB, 46755PB

## **Product Description**

White Rhino Rust Preventive is Slide's answer to processors looking for a great, NSF-certified rust preventive for their mold assemblies and machinery that produce food packaging. Its fast-drying formulation sets up quickly to protect immediately against moisture and light acids. It is self-cleaning in startup which saves time and money. White Rhino offers up to 2-years corrosion protection under normal indoor storage conditions.

Applications	Rust Preventive
Unit Package Description	1, 5 and 55-gallon containers
Generic Description	Rust Preventive
Approx. Net Weight Fill per Gal.	6 pounds
Net Weight Fill	1 - 55 gallons
Appearance	Brownish-Tint Liquid
Odor	Mild, Petroleum like
Flash Point F	25 degrees
Flash Point C	Negative 4 degrees
Base Type	Petroleum
Evaporation Rate	Slow
HMIS Rating	2, 3, 0, X
DOT Proper Shipping Name	UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II
VOC % (Federal)	81
VOC g/L (Federal)	887.91
VOC lbs./Gal (Federal)	7.41
Removal	Remove with organic or hydrocarbon solvents
Food Safety Citation (CFR)	NSF H1
Units Per Case	1
Case Weight (Ibs)	Various
Working Temperature F	32 to 350 degrees
Working Temperature C	0 to 176 degrees
Specific Gravity	0.698