

## TECHNICAL DATA SHEET



### Heavy-Duty 10% Mold Release Bulk/Liquid 54901HB, 54905HB, 54955HB

#### Product Description

Heavy-Duty 10% Mold Release provides Slide's highest percentage of active ingredients for a release agent. It is also widely used in conjunction with Slide's Super Grease Ejector Pin Grease on ejector pins. It's an ideal lubricant for the front half of ejector pins (pins in forward position). This product acts as a nearly dry lubricant minimizing the possibility of leaching out onto molded parts. Food-approved formulation that is paintable and non-silicone.

#### Applications

Mold Release

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Mold Release

#### Approx. Net Weight Fill per Gal.

7 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Clear Oily Colorless Liquid

#### Odor

Mild, Petroleum like

#### Flash Point F

25 degrees

#### Flash Point C

Negative 4 degrees

#### Base Type

Propylene Glycol

#### Evaporation Rate

Fast

#### HMIS Rating

2, 3, 0, X

#### DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

90

#### VOC g/L (Federal)

654.92

#### VOC lbs./Gal (Federal)

5.46

#### Removal

Remove with organic or hydrocarbon solvents

#### Food Safety Citation (CFR)

21CFR 178.3570

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 450 degrees

#### Working Temperature C

0 to 232 degrees

#### Specific Gravity

0.791