

## TECHNICAL DATA SHEET



### Paintable Mold Release Aerosol 40012N

#### Product Description

This Paintable Mold Release is UL recognized and requires no special cleaning. It will not interfere with part bonding, heat sealing, laminating, ultrasonic welding or post-decorating operations. You get perfect finishes every time and more cycles per can over other comparable releases. Extremely effective for investment wax casting, injection and compression molding.

#### Applications

Mold Release

#### Unit Package Description

16 ounce aerosol

#### Generic Description

Paintable Mold Release

#### Net Weight Fill

11.5 net ounces

#### UPC Code

858799000004

#### Appearance

Clear Oily Colorless Liquid

#### Odor

Ether like

#### Flash Point F

Not Applicable

#### Flash Point C

Not Applicable

#### Base Type

Paintable Silicone Fluid

#### Evaporation Rate

Fast

#### HMIS Rating

1, 3, 0, B

#### DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

#### VOC % (Federal)

60

#### VOC g/L (Federal)

441.96

#### VOC lbs./Gal (Federal)

3.68

#### Removal

Remove with organic or hydrocarbon solvents

#### Units Per Case

12

#### Case Weight (lbs)

13

#### Working Temperature F

32 to 650 degrees

#### Working Temperature C

0 to 343 degrees

#### Propellant

DME/152A

#### NFPA Aerosol Flammability Level

1

#### Independent Certifications

UL recognized