


TECHNICAL DATA SHEET



Regular Silicone Mold Release Bulk/Liquid 40101PB, 40105PB, 40155PB

Product Description Get more cycles per spray, more cycles per can, with

Slide's Silicone high-quality, pure silicone-oil mold release. Keeps the most challenging parts from hanging up and stalling production. Extremely effective for investment wax casting, injection and

compression molding.

Applications Mold Release

Unit Package Description 1, 5 and 55-gallon containers

Generic Description Silicone Mold Release

Approx. Net Weight Fill per Gal. 6 pounds

Net Weight Fill 1 - 55 gallons

Appearance Clear Oily Colorless Liquid

Odor Mild, Petroleum-like

Flash Point F 25 degrees

Flash Point C Negative 4 degrees

Base Type Silicone

Evaporation Rate Fast

HMIS Rating 2, 3, 0, X

DOT Proper Shipping Name UN1206, Proper Shipping Name - Heptanes Solution,

Hazard Class - 3, Packing Group - II

VOC % (Federal) 95

VOC g/L (Federal) 675.58

VOC lbs./Gal (Federal) 5.64

Removal Remove with organic or hydrocarbon solvents

Food Safety Citation (CFR) 21CFR 175.300

Units Per Case 1

Case Weight (lbs) Various

Working Temperature F 32 to 600 degrees

Working Temperature C 0 to 315 degrees

Specific Gravity 0.698





