

TECHNICAL DATA SHEET



No-Rust Rust Preventive Bulk/Liquid 40201B, 40205B, 40255B

Product Description

No-Rust® is a one-step rust preventive that contains both acid neutralizer and rust preventive. Its non-silicone, non-wax formulation provides positive protection by displacing moisture from metal surfaces and adhering tightly to the surface. It contains no chlorinated solvents and neutralizes finger print acids. Ideal for mold and die protection, it also works on stamping dies, stripper plates, jigs and fixtures, die casting dies, precision instruments, machine tools and machined or ground steel of all kinds. Provides up to 5-years of corrosion protection under normal indoor storage conditions.

Applications

Rust Preventive

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Rust Preventive

Approx. Net Weight Fill per Gal.

7 pounds

Net Weight Fill

1 - 55 gallons

Appearance

Brownish-Tint Liquid

Odor

Petroleum like

Flash Point F

160 degrees

Flash Point C

71.1 degrees

Base Type

Petroleum

Evaporation Rate

Slow

HMIS Rating

1, 2, 0, G

DOT Proper Shipping Name

Not Regulated

VOC % (Federal)

63

VOC g/L (Federal)

528.43

VOC lbs./Gal (Federal)

4.41

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

1

Case Weight (lbs)

Various

Working Temperature F

32 to 400 degrees

Working Temperature C

0 to 204 degrees

Specific Gravity

0.852