## SLIDE.

## **TECHNICAL DATA SHEET**



A synthetic wax release agent for epoxy resins, polyesters, phenolics and most other resins. Un agente desmoldante de cera sintética para resinas epoxidicas, polétstores, fendilcos y la mayoría de otras resinas.



## Epoxease Mold Release Aerosol 40614

## **Product Description**

EpoxEase is a synthetic wax-based, non-silicone release. It is formulated to prevent the sticking commonly seen when using all-purpose release agents on epoxies, maximizing your productivity. Ideal for use on epoxy, polyester and phenolic resins and most often utilized in encapsulating and potting applications.

Applications	Mold Release
Unit Package Description	16 ounce aerosol
Generic Description	Mold Release for Epoxy Resins
Net Weight Fill	14 net ounces
UPC Code	858799000066
Appearance	Light-brown Oily Wax
Odor	Petroleum like
Flash Point F	Not Applicable
Flash Point C	Not Applicable
Base Type	Wax
Evaporation Rate	Fast
HMIS Rating	2, 3, 0, B
DOT Proper Shipping Name	UN 1950, Aerosols, Flammable, 2.1, Limited Quantity
VOC % (Federal)	92.58
VOC g/L (Federal)	986.68
VOC lbs./Gal (Federal)	8.23
Removal	Remove with organic or hydrocarbon solvents
Units Per Case	12
Case Weight (Ibs)	15
Working Temperature F	32 to 450 degrees
Working Temperature C	0 to 232 degrees
Propellant	Propane
NFPA Aerosol Flammability Level	1

