

TECHNICAL DATA SHEET



Econo-Spray® 3 Mold Release Aerosol 40810P

Product Description

Econo-Spray® 3 contains a highly effective non-silicone release in a non-chlorinated solvent carrier system. This product is highly paintable, and will permit ultrasonic welding of molded parts. It affords excellent release of all thermoplastics.

Applications	Mold Release
Unit Package Description	16 ounce aerosol
Generic Description	Paintable Mold Release
Net Weight Fill	10 net ounces
UPC Code	858799000080
Appearance	Clear Oily Colorless Liquid
Odor	Mild, Petroleum like
Flash Point F	Not Applicable
Flash Point C	Not Applicable
Base Type	Propylene Glycol
Evaporation Rate	Fast
HMIS Rating	1, 4, 0, B
DOT Proper Shipping Name	UN 1950, Aerosols, Flammable, 2.1, Limited Quantity
VOC % (Federal)	97
VOC g/L (Federal)	613
VOC lbs./Gal (Federal)	5.12
Removal	Remove with organic or hydrocarbon solvents
Food Safety Citation (CFR)	21CFR 178.3570
Units Per Case	12
Case Weight (lbs)	12
Working Temperature F	32 to 600 degrees
Working Temperature C	0 to 315 degrees
Propellant	Propane
NFPA Aerosol Flammability Level	3