

## TECHNICAL DATA SHEET



### Penetrant Plus Bulk/Liquid 41801MB, 41805MB, 41855MB

#### Product Description

This mono-molecular penetrating film frees rust-frozen parts. It lifts and replaces moisture with a protective film and lubricates without affecting performance of electrical equipment. Non-conductive because it has high dielectric strength and lubricates delicate electronic equipment.

#### Applications

Penetrating Lubricant

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Penetrating Oil

#### Approx. Net Weight Fill per Gal.

7 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Brownish-Tint Liquid

#### Odor

Petroleum like

#### Flash Point F

207 degrees

#### Flash Point C

97 degrees

#### Base Type

Petroleum Oil with PTFE

#### Evaporation Rate

Slow

#### HMIS Rating

1, 1, 0, Not Determined

#### DOT Proper Shipping Name

Not Regulated

#### VOC % (Federal)

88

#### VOC g/L (Federal)

738.13

#### VOC lbs./Gal (Federal)

6.16

#### Removal

Remove with organic or hydrocarbon solvents

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 338 degrees

#### Working Temperature C

0 to 170 degrees

#### Specific Gravity

0.79