

TECHNICAL DATA SHEET



Quick Rust Preventive Bulk/Liquid 42801RPB, 42805RPB, 42855RPB

Product Description

Slide Quick RP employs a combination of fast evaporating solvents and oils to set up quickly on your mold surfaces, providing immediate protection against moisture and light acids. This unique "dry" package makes clean-up quick and easy when the mold is put back into production, saving time and money. The red tracing dye allows for visual verification of complete mold coverage. Offering up to 2-years corrosion protection under normal indoor storage conditions.

Applications

Rust Preventive

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Rust Preventive

Approx. Net Weight Fill per Gal.

6 pounds

Net Weight Fill

1 - 55 gallons

Appearance

Red-Tint Liquid

Odor

Mild, Petroleum like

Flash Point F

25 degrees

Flash Point C

Negative 4 degrees

Base Type

Lecithin

Evaporation Rate

Moderate

HMIS Rating

2, 3, 0, X

DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

VOC % (Federal)

87

VOC g/L (Federal)

625.49

VOC lbs./Gal (Federal)

5.22

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

1

Case Weight (lbs)

Various

Working Temperature F

32 to 350 degrees

Working Temperature C

0 to 176 degrees

Specific Gravity

0.698