

## TECHNICAL DATA SHEET



### Mold Shield Dry Rust Preventive Bulk/Liquid 42901PB, 42905PB, 42955PB

#### Product Description

Mold Shield® has a unique, extra-dry spray package, which delivers a dry, non-silicone, non-wax and non-penetrating protective coating onto the mold surface including ejector pin sleeves, slides, cams and other moving mold components. This special dry mist will not bleed out, and prevents marking of plastic parts when molds are put back into service. Offering self-cleaning action at production start-up, there's no need for cleaning it off with a solvent. Up to 2-years corrosion protection under normal indoor storage conditions.

#### Applications

Rust Preventive

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Rust Preventive

#### Approx. Net Weight Fill per Gal.

6 pounds

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Brown-tint Liquid

#### Odor

Mild, Petroleum-like

#### Flash Point F

25 degrees

#### Flash Point C

Negative 4 degrees

#### Base Type

Lecithin

#### Evaporation Rate

Moderate

#### HMIS Rating

2, 3, 0, X

#### DOT Proper Shipping Name

UN1206, Proper Shipping Name - Heptanes Solution, Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

87

#### VOC g/L (Federal)

625.49

#### VOC lbs./Gal (Federal)

5.22

#### Removal

Remove with organic or hydrocarbon solvents

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 350 degrees

#### Working Temperature C

0 to 176 degrees

#### Specific Gravity

0.698

