

TECHNICAL DATA SHEET



Super Grease Non-Aerosol

43900-01, 43900-03, 43900T, 43900-7, 43900-35,
43900-400

Product Description

Super Grease will not separate, run or fall out and has exceptional load-bearing properties. Thixotropic properties provide excellent mechanical stability when sudden temperature changes occur. A clear, clean, non-yellowing grease, Super Grease is ideal for injection molds, mold assemblies, and especially medical and food grade plastic parts. It also repels water and prevents corrosion.

Applications

Ejector Pin Lubricant

Unit Package Description

Multiple sizes

Generic Description

Ejector Pin Grease

Net Weight Fill

multiple sizes

UPC Code

858799000752

Appearance

Colorless Grease

Odor

None

Flash Point F

455 degrees

Flash Point C

235 degrees

Base Type

PTFE

Evaporation Rate

N/A

HMIS Rating

0, 1, 0, None Determined

DOT Proper Shipping Name

Not Regulated, Lubricating, NOI

Removal

Remove with organic or hydrocarbon solvents

Food Safety Citation (CFR)

NSF H1

Units Per Case

multiple sizes

Working Temperature F

-45 to 650 degrees

Working Temperature C

-43 to 343 degrees

Propellant

N/A

NFPA Aerosol Flammability Level

N/A

Independent Certifications

NSF category H1