

TECHNICAL DATA SHEET



Urethane Mold Release Aerosol 45812H

Product Description

Urethane mold release is extremely effective for all polyurethanes: rigid, semi-rigid and flexible urethane foams. Urethane mold release imparts a light, dry coating on the mold, eliminating build-up. Yet, it is so effective that it continues to work for several cycles between applications. Non-paintable formulation.

Applications	Mold Release
Unit Package Description	16 ounce aerosol
Generic Description	Mold Release for Urethane Resins
Net Weight Fill	11.5 net ounces
UPC Code	858799000585
Appearance	Clear Oily Colorless Liquid
Odor	Ether like
Flash Point F	Not Applicable
Flash Point C	Not Applicable
Base Type	Silicone
Evaporation Rate	Fast
HMIS Rating	1, 3, 0, B
DOT Proper Shipping Name	UN 1950, Aerosols, Flammable, 2.1, Limited Quantity
VOC % (Federal)	57.78
VOC g/L (Federal)	431.97
VOC lbs./Gal (Federal)	3.6
Removal	Remove with organic or hydrocarbon solvents
Units Per Case	12
Case Weight (lbs)	13
Working Temperature F	32 to 500 degrees
Working Temperature C	0 to 260 degrees
Propellant	DME/152A
NFPA Aerosol Flammability Level	1