


## TECHNICAL DATA SHEET



### Knock Out Mold Release Aerosol 46612N

#### Product Description

Knock Out gets "sticky parts" cleanly out of the mold and is approved for indirect food contact. It imparts a light, dry coating that is amazingly effective, working for several cycles without re-application. Paintable formulation.

#### Applications

Mold Release

#### Unit Package Description

16 ounce aerosol

#### Generic Description

Paintable Mold Release

#### Net Weight Fill

11.5 net ounces

#### UPC Code

858799000660

#### Appearance

Clear Oily Liquid

#### Odor

Ether like

#### Flash Point F

Not Applicable

#### Flash Point C

Not Applicable

#### Base Type

Propylene Glycol

#### Evaporation Rate

Fast

#### HMIS Rating

1, 3, 0, B

#### DOT Proper Shipping Name

UN 1950, Aerosols, Flammable, 2.1, Limited Quantity

#### VOC % (Federal)

60

#### VOC g/L (Federal)

438.39

#### VOC lbs./Gal (Federal)

3.65

#### Removal

Remove with organic or hydrocarbon solvents

#### Food Safety Citation (CFR)

21CFR 178.3570

#### Units Per Case

12

#### Case Weight (lbs)

13

#### Working Temperature F

32 to 450 degrees

#### Working Temperature C

0 to 232 degrees

#### Propellant

DME/152A

#### NFPA Aerosol Flammability Level 1