

TECHNICAL DATA SHEET



DuraKote™ Variation Mold Release Bulk/Liquid 52962-1, 52962-5, 52962-55

Product Description

DuraKote™ is a special air-drying release that will not transfer onto the molded part. It provides a dry, dust-free film on all hard-surfaced molds. It won't discolor and is paintable when it is baked on.

Applications	Mold Release
Unit Package Description	1, 5 and 55-gallon containers
Generic Description	Semi-Permanent Mold Release
Approx. Net Weight Fill per Gal.	7
Net Weight Fill	1 - 55 gallons
Appearance	Clear Oily Colorless Liquid
Odor	Mineral Spirits
Flash Point F	>100
Flash Point C	>38
Base Type	Curable Silicone Fluid
Evaporation Rate	Slow
HMIS Rating	1, 2, 0, G
DOT Proper Shipping Name	UN1993, Flammable liquids, n.o.s., (Isopropanol, Petroleum Distillates), Hazard Class - 3, Packing Group - II
VOC % (Federal)	96
VOC g/L (Federal)	824.95
VOC lbs./Gal (Federal)	6.05
Removal	Remove with organic or hydrocarbon solvents
Units Per Case	1
Case Weight (lbs)	Various
Working Temperature F	32 to 600 degrees
Working Temperature C	0 to 315 degrees
Specific Gravity	0.788