

TECHNICAL DATA SHEET



DuraKote™ Variation Mold Release Bulk/Liquid 52962-1, 52962-5, 52962-55

Product Description

DuraKote™ is a special air-drying release that will not transfer onto the molded part. It provides a dry, dust-free film on all hard-surfaced molds. It won't discolor and is paintable when it is baked on.

Applications

Mold Release

Unit Package Description

1, 5 and 55-gallon containers

Generic Description

Semi-Permanent Mold Release

Approx. Net Weight Fill per Gal.

7

Net Weight Fill

1 - 55 gallons

Appearance

Clear Oily Colorless Liquid

Odor

Mineral Spirits

Flash Point F

>100

Flash Point C

>38

Base Type

Curable Silicone Fluid

Evaporation Rate

Slow

HMIS Rating

1, 2, 0, G

DOT Proper Shipping Name

UN1993, Flammable liquids, n.o.s., (Isopropanol, Petroleum Distillates), Hazard Class - 3, Packing Group -II

VOC % (Federal)

96

VOC g/L (Federal)

824.95

VOC lbs./Gal (Federal)

6.05

Removal

Remove with organic or hydrocarbon solvents

Units Per Case

1

Case Weight (lbs)

Various

Working Temperature F

32 to 600 degrees

Working Temperature C

0 to 315 degrees

Specific Gravity

0.788