

## TECHNICAL DATA SHEET



### DuraKote™ Variation Mold Release Bulk/Liquid 52962-1, 52962-5, 52962-55

#### Product Description

DuraKote™ is a special air-drying release that will not transfer onto the molded part. It provides a dry, dust-free film on all hard-surfaced molds. It won't discolor and is paintable when it is baked on.

#### Applications

Mold Release

#### Unit Package Description

1, 5 and 55-gallon containers

#### Generic Description

Semi-Permanent Mold Release

#### Approx. Net Weight Fill per Gal.

7

#### Net Weight Fill

1 - 55 gallons

#### Appearance

Clear Oily Colorless Liquid

#### Odor

Mineral Spirits

#### Flash Point F

>100

#### Flash Point C

>38

#### Base Type

Curable Silicone Fluid

#### Evaporation Rate

Slow

#### HMIS Rating

1, 2, 0, G

#### DOT Proper Shipping Name

UN1993, Flammable liquids, n.o.s., (Isopropanol, Petroleum Distillates), Hazard Class - 3, Packing Group - II

#### VOC % (Federal)

96

#### VOC g/L (Federal)

824.95

#### VOC lbs./Gal (Federal)

6.05

#### Removal

Remove with organic or hydrocarbon solvents

#### Units Per Case

1

#### Case Weight (lbs)

Various

#### Working Temperature F

32 to 600 degrees

#### Working Temperature C

0 to 315 degrees

#### Specific Gravity

0.788